

MT MASS TRANSFER

July 08, 14

Mass Transfer

Transfer of mass from one pt. to another in a single phase or from one phase to another with the help of a driving force is known as Mass Transfer.

The driving force here is mainly the concⁿ diff.

Mass transfer takes place in every case partial pressure diff, temp. diff, Magnetic field diff. Bt amount of transfer is negligible so we consider only concⁿ diff.

* The main driving force of M.T is chemical potential diff.

Types of Mass Transfer

i) Molecular diffusion:- The transfer of mass (molecules) or diffusion of a species takes place in a ~~turb~~ stagnant medium.

* If there is a turbulent diffusion, then there must be molecular diffusion.

ii) Turbulent or Eddy diffusion:- If the diffusion of species takes place in a turbulent medium, then the mechanism is known as turbulent or eddy diffusion.

Molecular diffusion occurs due to motion & motion is microscopic bt in turbulent diffusion motion is macroscopic.

Some imp. things to remember:-

$S_i \Rightarrow$ mass concentration of i th species in a solution (kg/m^3)

$S \Rightarrow$ total mass " " all " " " " " (kg/m^3)

$w_i = \frac{S_i}{S} \Rightarrow$ mass fraction of the i th species in the solution. (unitless)

$C_i \Rightarrow$ Molar concentration of the i th species in the solⁿ (kmol/m^3)

$C \Rightarrow$ total molar concentration of all the species in the solⁿ (kmol/m^3)

$x_i = \frac{C_i}{C} \Rightarrow$ Mole fraction of the i th species in the solution.

$$\sum S_i = S$$

$$\sum C_i = C$$

$$\sum x_i = 1$$

$$\sum w_i = 1$$



$$y_i = \frac{P_i}{P} = \frac{\text{Partial pressure } i^{\text{th}} \text{ species}}{\text{total pressure.}}$$

Mass avg. velocity:- (u)

$$u = \frac{\sum \beta_i u_i}{\sum \beta_i = 1} \quad \text{or} \quad u = \sum w_i u_i$$

Unit = m/s

u_i = linear velocity of i^{th} species.

Molar avg Velocity :- (U)

$$U = \frac{\sum c_i u_i}{\sum c_i} \quad \text{or} \quad U = \sum x_i u_i$$

Flux: —

The net rate at which a species in a solution passes through unit area, which is normal to the direction of diffusion in unit time.

$\text{Kg/m}^2\text{s}$, $\text{kmol/m}^2\text{s}$
mass flux , molar flux.

Mans flux :- (denoted by small letter)

N_i = Mass flux of the i^{th} species w.r.t a stationary observer
 $= \dot{S}_i (U_i - 0)$ $\rightarrow$ denotes observer is stationary.
 $= \text{Kg/m}^2 \text{s}.$

i_i = Mass flux of the i th species w.r.t an observer moving with mass avg. velocity.

$$= g_i (\hat{u}_i - u)$$

$j_i =$ Mass flux of the i th species w.r.t an observer moving with molar avg. velocity.

$$= k_a / m^2 s$$

Molar flux:- (denoted by capital letters)

$$N_i = C_i (u_i - 0)$$

$$I_i = C_i (u_i - u)$$

$$J_i = C_i (u_i - U)$$

$$J_i = C_i (u_i - U)$$

$$\sum J_i = \sum C_i (u_i - U)$$

$$= \sum C_i u_i - \sum C_i U$$

$$= \frac{C \sum C_i u_i}{C} - \sum C_i U$$

$$= C U - C U$$

*

$$\boxed{\sum J_i = 0}$$

★ The total molar flux of all the species of a solution wrt an observer moving with molar avg. velocity is zero.

$$i_i = f_i (u_i - u)$$

$$\sum i_i = \sum f_i (u_i - u)$$

$$\sum i_i = \sum f_i u_i - \sum f_i u$$

$$= f \frac{\sum f_i u_i}{f} - \sum f_i u$$

$$= f u - f u$$

$$\boxed{\sum i_i = 0}$$

★ Mass flux of all the species in a solution wrt an observer moving with mass avg. velocity is zero.

When there is mass-mass, mole-mole symmetry flux will be zero, otherwise flux will not be zero.

$$\boxed{\begin{array}{l} i_1 + i_2 = 0 \\ J_1 + J_2 = 0 \\ N_1 + N_2 \neq 0 \end{array}}$$

Fick's first law:-

The molar flux of a species wrt. an observer moving with molar avg. velocity is directly proportional to the gradient of the concentration of that species.

$$J_A \propto \frac{dC_A}{dz}$$

If we remove the proportionality, then the constant of proportionality must be introduced, which is known as diffusivity or diffusion coeff, denoted by D_{AB} for a binary mixture or D_{ij} for a multicomponent mixture. This coeff. tell us how easily species i diffuse in the solution, or for a binary mixture how easily A diffuses into B .

$$J_{A_z} = -D_{AB} \frac{dC_A}{dz}$$

-ve sign represents the transfer of mass taking place from a region of higher concentration to a region of lower concentration.

if diffusion is defined for 1 dirn
complete derivative is used.
if diffusion is defined for more
than 1 dirn, partial derivative
is used.

$$\frac{\text{kmol}}{\text{m}^2\text{s}} \leftarrow \underbrace{J_{A_z}}_{\text{quantity}} = -D_{AB} \underbrace{\frac{\partial C_A}{\partial z}}_{\text{gradient}} \rightarrow \frac{\text{kmol}}{\text{m}^2\text{s}}$$

$\downarrow$
 m^2/s

quantity = gradient.

Fourier Law:-

$$\frac{\text{kJ}}{\text{m}^2\text{s}} \leftarrow q_z = -k \frac{dT}{dz} \rightarrow \text{C, } k$$

$$\frac{\text{kJ}}{\text{m}^2\text{s}} \leftarrow q_z = \frac{-k}{\beta_{cp}} \frac{dT\beta_{cp}}{dz} \rightarrow \frac{\text{kJ}}{\text{m}^2\text{s}}$$

$$\boxed{q_z = -\alpha \frac{d\beta_{cp}T}{dz}}$$

$\downarrow$
 m^2/s

Analogy with Fick's law

Momentum diffusivity :-

$$\tau = -\mu \frac{dv}{dz}$$

Momentum flux

Momentum $\rightarrow \text{kg m/s}$
 $\text{m}^2 \cdot \text{s}$

$\tau \rightarrow \text{m}^2/\text{s}$

$$T_{yz} = -\frac{\mu}{\rho} \frac{dv_y}{dz}$$

not a vector
it is tensor

momentum
 m^3

* basic diff mass flux & heat flux is a vector and momentum flux is tensor.

Every quantity is a tensor quantity but of different order like pressure is tensor of zero order because its value is same in all the direction.


Like stress tensor of second order it is applied in two particular direction.

$$J_A = -D_{AB} \frac{dC_A}{dz}$$

$$q_z = -\alpha \frac{dT}{dz}$$

$$T_{yz} = -\frac{\mu}{\rho} \frac{dv_y}{dz}$$

The basic diff in between 3 is that the molar flux & heat flux are vectors or tensor of first order but momentum flux is a tensor of second order.



(diff in densities)
(Mass is same)

(Uniform concentration)

In the first diagram if we put the wt. balance at the partition, then both side are on equal level. If we remove the partition and give sufficient tym to the system so that at each pt., If the wt. balance is in the same position as previously then the system will tilt on the left. This shows that the net rate of flux is ~~in~~ ⁱⁿ the direction of right to left.

$$* * \quad N_A = J_A + N x_A \quad \rightarrow -D_A \frac{dC_A}{dz}$$

The flux of any species is the sum of convective transport and molecular transport.

$$\begin{aligned} J_A &= C_A (U_A - U) \\ &= C_A U_A - C_A U \\ &= N_A - C_A \left(\frac{C_A U_A + C_B U_B}{C_A + C_B} \right) \\ &= N_A - \underbrace{C_A \frac{(N_A + N_B)}{C}} \end{aligned}$$

$$= N_A - x_A N \quad \rightarrow -C D_{AB} \frac{dx_A}{dz}$$

$$N_A = J_A + N x_A$$

$$N_A = J_A + N \frac{C_A}{C} \quad \rightarrow -D_{AB} \frac{dC_A}{dz} \quad \left\{ \begin{array}{l} x_A = C_A/C \\ -C D_{AB} \frac{dC_A}{dz} \end{array} \right.$$

$$N_A = J_A + N \frac{P_A}{P} \quad \rightarrow -\frac{D_{AB}}{RT} \frac{dP_A}{dz} \quad \left[\begin{array}{l} C = \frac{P}{RT} \\ x_A = \frac{P_A}{P} \end{array} \right]$$

★ In Heat transfer, there is only one driving force i.e temp. difference but in Mass transfer, there are more than one driving forces like concentration gradient, mole fraction gradient, partial pressure gradient etc.

⇒ Driving force also tells us how far a system is from equilibrium.

$$N_A = J_A + N x_A$$

$$N_B = J_B + N x_B$$

$$N_A + N_B = J_A + J_B + N(x_A + x_B)$$

$$N = J_A + J_B + N$$

$$J_A + J_B = 0$$

$$J_A = -J_B$$

$$-(-D_{AB} \frac{dc_A}{dz}) = -(-D_{BA} \frac{dc_B}{dz})$$

$$D_{AB} = D_{BA}$$

Assumption
 $c_A + c_B = C$
 $\frac{dc_A}{dz} + \frac{dc_B}{dz} = 0$
 $\frac{dc_A}{dz} = -\frac{dc_B}{dz}$

Diffusivity in a binary system are equal to each other for the ideal case when total concentration is constant. Diffusivity are directional dependent for all the cases except the ideal case.

Diffusional Velocity of species A (Relative Velocity):—

$$C_A(U_A - U) = J_A = -D_{AB} \frac{dc_A}{dz}$$

$$U_A - U = -\frac{D_{AB}}{C_A} \frac{dc_A}{dz}$$

July 09, 2014

~~Q.1~~

$$N_{A1} = N_{A2}$$

$$\frac{N_{A1}}{N_{A2}} = \frac{r_2}{r_1}$$

$$\frac{N_{A1}}{N_{A2}} = \frac{r_2^2}{r_1^2}$$

for rectangular slab

for cylindrical

for sphere.

Rate of H.T in a given area whether constant or changing is always constant but flux will change if the area change.

* If there is box, whose radius at bottom is 20, middle is 10 and top is 5 and above that is air. Then flux at top is more.

Diffusion of A through Non-diffusing B

Liquid A is evaporating into gas B. We imagine that there is some device that maintains the liquid level at $z=0$. Solubility of gas B in liquid A is negligible or B is non-diffusing. A stream of gas mixture A+B having concentration x_{A2} flows slowly over the top of the tube to maintain the mole fraction of A at x_{A2} . Entire system is kept at constant temp. and pressure. Gases A & B are assumed to be ideal.

$$N_A = N x_A + J_A \quad \text{--- } (N_A + N_B)$$

$$N_A = N x_A - C_{DAB} \frac{dx_A}{dz}$$


$$N_A (1 - x_A) = -C_{DAB} \frac{dx_A}{dz}$$

$$N_A \int_0^z dz = -C_{DAB} \int_{x_{A1}}^{x_{A2}} \frac{dx_A}{(1-x_A)}$$

$$N_A z = C_{DAB} \ln \left| \frac{1-x_{A2}}{1-x_{A1}} \right|$$

$$x_{A1} - x_{A2} = x_{B2} - x_{B1}$$

$$N_A = \frac{C_{DAB}}{z} \frac{x_{B2} - x_{B1}}{\ln \left(\frac{x_{B2}}{x_{B1}} \right)}$$



$$N_A = \frac{C_{DAB}}{z} \frac{x_{A1} - x_{A2}}{x_{BLM}}$$

$$x_{BLM} = \frac{x_{B2} - x_{B1}}{\ln(x_{B2}/x_{B1})}$$

When the diff b/w two concentration x_{B2} & x_{B1} is very less then we take the arithmetic mean not the logarithm mean.

$$x_A = C_A / C$$

$$N_A = \frac{D_{AB}}{z} (C x_{A1} - C x_{A2})$$

$$x_{BLM} = \frac{x_{B2} - x_{B1}}{\ln \frac{x_{B2}}{x_{B1}}}$$

Arithmetic mean tell only initial & final state but LMTD tells us in b/w diff also.

$$C_{BLM} = \frac{C_{B2} - C_{B1}}{C_+} \frac{1}{\ln(C_{B2}/C_{B1})}$$

$$N_A = \frac{C D_{AB}}{z} \frac{C_{A1} - C_{A2}}{C_{BLM}}$$

$$N_A = \frac{C D_{AB}}{z} \frac{P_{A1} - P_{A2}}{P_{BLM}}$$

$$x_A = \frac{P_A}{P}$$

$$P_{BLM} = \frac{P_{B2} - P_{B1}}{P} \frac{1}{\ln \frac{P_{B2}}{P_{B1}}}$$

$$N_A = \frac{P D_{AB}}{RT z} \frac{P_{A1} - P_{A2}}{P_{BLM}}$$



Equimolar Counter diffusion:- EMCD

$$N_A = (N_A + N_B) x_A + J_A$$

$$N_A = -N_B$$

$$N_A = J_A = -C D_{AB} \frac{dx_A}{dz}$$

$$N_A = \frac{C D_{AB}}{z} (x_{A1} - x_{A2})$$

In the case of diffusion of A from non-diffusing B, by governing

eqn $N_A = \underbrace{N_A x_A}_{\text{Bulk term}} + \underbrace{J_A}_{\text{Molecular term}}$

bcz of bulk term diffusion takes place & J_A ki wajah se bhi diffusion ho rahi hai uski flux jada hogi

For the case of EMCD, my governing eqn is $N_A = J_A$

So, in the first case flux will be more bcz of the presence of bulk motion.

Diffusion of a spherical naphthalene ball in air:—

$$N_A = N_A + N_B \rightarrow N_A + N_B = 0$$

$$N_A = N_A + J_A$$

$$N_A (1 - x_A) = J_A$$

$$N_A (1 - x_A) = -C_{DAB} \frac{dx_A}{dr}$$

$$\frac{W_A}{4\pi r^2} (1 - x_A) = -C_{DAB} \frac{dx_A}{dr}$$

$$\frac{W_A}{4\pi} \int_{r_1}^{r_2} \frac{dr}{r^2} = -C_{DAB} \int_{x_{A1}}^{x_{A2}} \frac{dx_A}{1 - x_A}$$

$$\frac{W_A}{4\pi} \left[\frac{1}{r_2} - \frac{1}{r_1} \right] = +C_{DAB} \ln \left| \frac{1 - x_{A2}}{1 - x_{A1}} \right|$$

$$\frac{W_A}{4\pi} \left[\frac{1}{r_2} - \frac{1}{r_1} \right] = C_{DAB} \frac{x_{A1} - x_{A2}}{x_{B1M}} \quad \text{governing eqn}$$

$$\frac{1}{r_2} \approx 0$$

$r_2 \approx$ radius of air
= infinity

$$\frac{W_A}{4\pi r_1^2} = \frac{C_{DAB}}{r_1} \frac{x_{A1} - x_{A2}}{x_{B1M}}$$

$$N_A|_{r=r_1} = \frac{C_{DAB}}{r_1} \frac{x_{A1} - x_{A2}}{x_{B1M}}$$

$$N_A|_{r=r_1} = \frac{P_{DAB}}{RT r_1} \frac{P_{A1} - P_{A2}}{P_{B1M}}$$

July 10, 14

The radius of the naphthalene ball decreases with time, but still we have taken it as steady state condition bcz it satisfies assumption of pseudo steady state diffusion.

Pseudo steady state:—

- ⇒ The diffusional rate should be very small.
- ⇒ The species which is diffusing should be very small in comparison to the species in which it is diffusing.

Time taken for the complete evaporation of a naphthalene ball:-

$$t=0, \quad y=y_1$$

$$t=t_f, \quad y=0$$

$$\frac{y_1}{2} \frac{\rho}{M} \frac{1}{N_A}$$

$$N_A = \frac{\text{kmol}}{\text{m}^2 \text{s}} = \frac{\rho}{M} \frac{dy}{dt} - \frac{\text{kmol}}{\text{m}^2 \text{s}}$$

$$N_A = \frac{\rho}{M} \frac{dy}{dt}$$

$$\boxed{N_A \frac{dy}{dt} = \frac{\rho}{M} \frac{dy}{dt}}$$



$$-\frac{W_A}{4\pi r^2} \left[\frac{1}{y_2} - \frac{1}{y_1} \right] = \frac{C_{DAB}}{\delta} \frac{(x_{A1} - x_{A2})}{x_{BLM}}$$

$$-\frac{W_A}{4\pi r^2} \frac{1}{y_2} \frac{1}{y_1} = \frac{C_{DAB}}{\delta} \frac{(x_{A1} - x_{A2})}{x_{BLM}}$$

Multiply y_1

$$-N_A = \frac{C_{DAB}}{\delta} \frac{(x_{A1} - x_{A2})}{x_{BLM}}$$

$$-\int_{y_1}^0 y dy = \frac{M C_{DAB}}{\rho} \frac{x_{A1} - x_{A2}}{x_{BLM}} \int_0^{t_f} dt$$

$$-\frac{y^2}{2} \Big|_{y_1}^0 = \frac{M C_{DAB}}{\rho} \frac{x_{A1} - x_{A2}}{x_{BLM}} \Big|_0^{t_f}$$

$$\boxed{t_f = \frac{y_1^2}{2} \frac{\rho}{M C_{DAB}} \frac{x_{BLM}}{x_{A1} - x_{A2}}}$$

$$\boxed{t_f = \frac{y_1^2}{2} \frac{\rho R T}{M P_{DAB}} \frac{P_{BLM}}{P_{A1} - P_{A2}}}$$

Diffusion in liquids :-

Case I :- Diffusion of A through non-diffusing B.

$$N_A = \frac{C}{z} D_{AB} \frac{(x_{A1} - x_{A2})}{x_{B1} M}$$

Car. $z = \frac{(C_1) + (C_2)}{2}$

$\left(\frac{g}{M}\right)_{avg} = \frac{\left(\frac{g}{M_1}\right) + \left(\frac{g}{M_2}\right)}{2}$

$M = M_1 M_2$

Case II :- EMCD

$$N_A = \frac{C D_{AB}}{z} (x_{A1} - x_{A2})$$

$$C \Rightarrow \left(\frac{g}{M}\right)_{avg} = \frac{\left(\frac{g}{M_1}\right) + \left(\frac{g}{M_2}\right)}{2}$$

Diffusion in Solids :-

Rates are slow in comparison to liquids and gases but it is important to us in many mass transfer operations.

ex $\rightarrow$ leaching of foods such soybean, crystallization, drying and many more.

Types :-

It is of two types.


i) Diffusion that can be considered to follow Fick's law and doesn't depend on the actual structure of solid.

for ex $\rightarrow$ In leaching the solid contains a large amount of water & solute is diffusing through this solution.

ii) Diffusion in porous solid where the actual structure and the voids are important.

$$N_A = \frac{\epsilon}{z} D_{AB} \frac{dC}{dz}$$

ϵ = voidage (fraction of voids in solid)
 z = Tortuosity




Unsteady state diffusion:-

$$\frac{\partial^2 C_A}{\partial x^2} = \frac{1}{D_{AB}} \frac{\partial C_A}{\partial t}$$

Fick's second law

Knudsen diffusion:-


Case-I when mean free path is greater than pore dia
 $\lambda \gg d$



Knudsen law

Case-II

$\lambda < d$



Fick's law

$$J_k = -D_k \frac{dC_A}{dz}$$

Knudsen law

D_k = Knudsen diffusivity.

$$= \frac{2}{3} \gamma_p V_T$$

γ_p = radius of passage

$$V_T = \left(\frac{8RT}{\pi M} \right)^{1/2} \text{ velocity of particle.}$$

$$D_k = 97.0 \gamma_p \left(\frac{T}{M} \right)^{1/2}$$

$$= 97.0 \times 60 \times 10^{-10} \left(\frac{373}{1} \right)^{1/2}$$

Diffusion in open system:-

If diffusion in porous solids or channels with no chemical reaction is occurring where total pressure P remains constant. Then for an open binary system.

$$\frac{N_A}{N_B} = - \sqrt{\frac{M_B}{M_A}}$$

Diffusivity dependence: -

For the gases, diffusivity is inversely proportion to the pressure, and diffusivity is directly proportion to $(\text{temp})^{3/2}$.

$$D_A \propto \frac{1}{p}$$


$$D_A \propto T^{3/2}$$

For the liquids

$$D_{AB} \propto T$$

for pressure = No dependence.

Counter diffusion: -



$$\frac{-\delta A}{n} = \frac{-\delta B}{m} = \frac{\delta C}{p}$$

$$\frac{+N_A}{-n} = \frac{N_B}{-m} = \frac{N_C}{p}$$

Ex →



find the relationship b/w fluxes of A & B.

$$\frac{N_A}{-1} = \frac{N_B}{2}$$

$$N_B = -2N_A$$



July 11, 14

Mass Transfer Coefficient:-

The rate of M-T is proportional to the driving force and also proportional to the area.

$$W_A \propto A \Delta C$$

$$W_A = (K_c) A \Delta C$$

→ M-T coeff.

$$N_A = \frac{W_A}{A} = K_c \Delta C$$

Unit $K_c \approx m/s$

$$\approx C_A (U_A - 0)$$

Like H-T coeff, it is also an experimental quantity and it can be calculated with the help of dimensionless numbers.

For gases:- (diffusion of A through non-diffusing B)

$$N_A = \frac{C D_{AB}}{z} \frac{C_{A1} - C_{A2}}{C_{BLM}}$$

Concentration terms.

$$N_A \approx K_c (C_{A1} - C_{A2})$$

$$= \frac{C D_{AB}}{z} \frac{(y_{A1} - y_{A2})}{y_{BLM}}$$

! mole fraction for gases so y term.

$$N_A \approx K_y (y_{A1} - y_{A2})$$

$$\approx \frac{P D_{AB}}{RT z} \frac{(P_{A1} - P_{A2})}{P_{BLM}}$$

$$N_A \approx K_G (P_{A1} - P_{A2})$$

$$N_A \approx \frac{D_{AB}}{z} \frac{(C_{A1} - C_{A2})}{X_{BLM}}$$

↓
 K_c

No C term, bcz V_{BLM} is not change in case so C term with D_{AB} is not written.

$$N_A \approx \frac{D_{AB}}{RT z} \frac{P_{A1} - P_{A2}}{X_{BLM}}$$

↓
 K_G

Here we put $C = P/RT$ so RT take separately

$$K_c = \frac{D_{AB}}{z \cdot x_{BLM}}$$

$$K_y = \frac{C D_{AB}}{z \cdot y_{BLM}}$$

$$K_G = \frac{D_{AB}}{RT z \cdot x_{BLM}}$$

* When I calculate M-T coeff, we will not change the term x_{BLM} to C_{BLM} or P_{BLM}

$$* \quad K_G = \frac{K_y}{P} = \frac{K_c}{RT}$$

For Liquids:-

$$N_A = \frac{C_{av} D_{AB}}{z} \frac{(x_{A1} - x_{A2})}{x_{BLM}} \Rightarrow K_N = \frac{C_{av} D_{AB}}{z \cdot x_{BLM}}$$

$$N_A = \frac{D_{AB}}{z} \frac{(C_{A1} - C_{A2})}{x_{BLM}} \Rightarrow K_L = \frac{D_{AB}}{z \cdot x_{BLM}}$$

$$* \quad K_N = \frac{K_L}{C_{av}}$$

For gases and liquids, equimolar counter diffusion:-

for gases

$$N_A = \frac{C D_{AB}}{z} (x_{A1} - x_{A2})$$

$$K'_y = \frac{C D_{AB}}{z}$$

$$N_A = \frac{D_{AB}}{z} (C_{A1} - C_{A2})$$

$$K'_c = \frac{D_{AB}}{z}$$

$$N_A = \frac{D_{AB}}{zRT} (P_{A1} - P_{A2})$$

$$K'_G = \frac{D_{AB}}{zRT}$$

$$* \quad K'_G = \frac{K'_c}{RT} = \frac{K'_y}{P}$$

for liquid.

$$N_A = \frac{C_{av} D_{AB}}{z} (x_{A1} - x_{A2})$$

$$K'_N = \frac{C_{av} D_{AB}}{z}$$

$$N_A = \frac{D_{AB}}{z} (C_{A1} - C_{A2})$$

$$K'_L = \frac{D_{AB}}{z}$$

$$* \quad K'_N = \frac{K'_L}{C_{av}}$$

For the dissolution of sphere in a flowing liquid ; MT coeff will depend upon

- i) The velocity of the liquid
- ii) Density of the liquid
- iii) Viscosity of the liquid
- iv) diffusivity of sphere into liquid.
- v) diameter

$$K = K_1 v^a \rho^b \mu^c D_{AB}^d D^e$$

$$\left[\frac{L}{T}\right]^1 = K_1 \left[\frac{L}{T}\right]^a \left[\frac{M}{L^3}\right]^b \left[\frac{M}{LT}\right]^c \left[\frac{L^2}{T}\right]^d [L]^e$$

for L

$$1 = a - 3b - c + 2d + e$$

for T

$$-1 = -a - c - d$$

for M

$$0 = b + c$$

Calculating the value of d, e, b in terms of (a, c)

$$b = -c$$

$$d = 1 - a - c$$

$$e = a - 1$$

put the values of constant.

$$\left[\frac{K}{\rho}\right]^1 = K [v]^a \frac{[\rho]}{\rho_a} \left[\frac{\mu}{\mu_a}\right]^c [D_{AB}]^{1-a-c} [D]^{a-1}$$

$\xrightarrow{\frac{D_{AB}}{(D_{AB})^{a+c}}}$

$$\left(\frac{K}{D_{AB}}\right) = \left(\frac{v \rho D}{\mu}\right)^a \left(\frac{\mu}{D_{AB} \rho}\right)^{a+c}$$

$$\downarrow$$

$$\boxed{Sh = (Re)^a (Sc)^{c'}}$$

We can say that

$$\boxed{Sh = a (Re)^a (Sc)^c}$$

Nusselt Number :- Convective heat flux divided by heat flux for conduction through a stagnant medium of thickness L for the same temp. diff.

$$Nu = \frac{h(\Delta T)}{\frac{k}{L}(\Delta T)} = \frac{hL}{k}$$

Analogy of nusselt number in mass transfer is sherwood no.

Sherwood Number :-

It is equal to convective molar flux divided by molar flux for molecular diffusion through a stagnant medium of thickness L , under the driving force of pressure difference.

$$Sh = \frac{K_G \Delta P}{\left(\frac{P_{DAB}}{ZRT} \frac{P_{A1} - P_{A2}}{P_{M}} \right)}$$

$$= \frac{K_G \cdot ZRT \cdot P_{M}}{P_{DAB}}$$

for dilute solⁿ
 $P_M = P$
 $P_{A1} = P_{A2}$
 $P = P_{A2} = P_{B2}$
 $\frac{P_{A1} - P_{A2}}{P_{M}} = \frac{P_{A1} - P_{A2}}{P}$
 $\frac{P_{A1} - P_{A2}}{P} = \frac{P_{A1} - P_{A2}}{P}$
 $\frac{P_{A1} - P_{A2}}{P} = \frac{P_{A1} - P_{A2}}{P}$

Assume dilute solution,

$$= \frac{K_G ZRT P}{P_{DAB}}$$

$$= \frac{K_G RT Z}{D_{AB}}$$

$$= \frac{K_c Z}{D_{AB}}$$

Prandtl number (Pr) :- It is defined as the ratio of momentum diffusivity by thermal diffusivity.

$$Pr = \frac{\nu}{\alpha} = \frac{\mu/\rho}{\frac{k}{\rho C_p}} = \frac{C_p \mu}{k}$$

Analogy of Prandtl number is Schmidt number no.

Schmidt Number:-

It is given by momentum diffusivity by mass diffusivity.

$$= \frac{\nu}{D_{AB}}$$

ex

$$Nu = 23 Re^3 \cdot Pr^8$$

$$Sh = 23 Re^3 \cdot Sc^8$$

* GENERAL VALUES OF M.T.C & DIFFUSIVITIES

M.T.C for gases :- $K_G = 10^{-2} \text{ m/s}$

for liquids :- $K_L = 10^{-5} \text{ m/s}$

diffusivities

liquid phase diffusivity

$$D_{AB/L} = 10^{-9} \text{ m}^2/\text{s}$$

gas phase diffusivity

$$D_{AB/G} = 10^{-5} \text{ m}^2/\text{s}$$

Turbulent or Eddy diffusion:-

It is defined as rapid and highly irregular fluctuations of velocities at any pt. in the fluid. Some fluid elements move randomly and are responsible for high rate of transport of momentum, heat & mass. These elements are known as eddies. To study these motion, fundamental laws are extended by replacing D_{AB} with eddy transport diffusion.

$$J_{A, \text{Turbulent}} = -E_D \frac{dC_A}{dz}$$

$$J_{A, \text{Total}} = - (D_{AB} + E_D) \frac{dC_A}{dz} \rightarrow C_{A1} - C_{A2}$$

molecular + turbulent

$$K = \frac{D_{AB} + E_D}{z_2 - z_1}$$

$\downarrow$ K

July 15, 14

Reynolds Analogy

$$\frac{Q}{A} = -\rho c_p (\alpha + \alpha_D^{\text{turbulent}}) \frac{dT}{dz}$$

$$\tau = -\rho \left(\frac{\mu}{3} + \nu_D \right) \frac{dv}{dz}$$

$$\frac{\tau}{Q/A} = \frac{1}{c_p} \frac{dv}{dT}$$

$$\frac{\tau}{Q/A} \cdot c_p \cdot dT = dv$$

$$\frac{\tau}{Q/A} c_p \int_{T_i}^T dT = \int dv$$

$$\frac{\tau}{Q/A} c_p (T - T_i) = v$$

$$\frac{Q}{A} = h (T - T_i)$$

$$f = \frac{\tau}{\frac{1}{2} \rho v^2}$$

$$\tau = \frac{1}{2} f \rho v^2$$

$$\frac{\frac{1}{2} f \rho v^2}{h (T - T_i)} c_p (T - T_i) = v$$

$$\boxed{\frac{f}{2} = \frac{h}{\rho c_p v}}$$

$$\boxed{\frac{f}{2} = \frac{h}{G c_p}}$$

$$\tau = -\rho (\nu + \nu_D) \frac{dv}{dz}$$

$$N_A = -(D_{AB} + E_D) \frac{dc_A}{dz}$$

Reynold's analogy is valid for turbulent

$$\alpha_D \approx \nu_D$$

$$\nu \ll \nu_D$$

$$\alpha \ll \alpha_D$$

* Molecular diffusivity is too much less than turbulent diffusivity

τ = momentum flux,
 Q/A = heat flux

$\therefore$ their ratio is always a constant quantity.

Convection

Fanning friction factor:

$$f v = G \text{ (mass velocity)}$$

was for momentum & heat

Assumption

$$\nu \ll \nu_D$$

$$E_D \approx \nu_D$$

$$D_{AB} \ll E_D$$

$$\frac{I}{N_A} = \int \frac{dv}{dca}$$

$$\frac{I}{N_A} \int_{c_{Ai}}^{c_A} dca = \int_0^V dv$$

$$\frac{I}{N_A} \cdot \frac{1}{\delta} (c_A - c_{Ai}) = V$$

$$\frac{1}{2} \frac{\delta v^2}{\delta K_c (c_A - c_{Ai})} (c_A - c_{Ai}) = V$$

$$\boxed{\frac{1}{2} = \frac{K_c}{V}}$$

→ It is valid when pratt no = schmidt no = 1

→ It is not valid for viscous sublayer, where the molecular diffusivities become important.

$$\boxed{\frac{1}{2} = \frac{h}{\delta v_{cp}} = \frac{K_c}{V}}$$

Chilton Colburn Analogy :-

It is valid for both turbulence & laminar.

$$\boxed{\frac{1}{2} = \underbrace{\frac{h}{\delta c_{pv}} (Pr)^{2/3}}_{J_H} = \underbrace{\frac{K_c}{V} (Sc)^{2/3}}_{J_D}}$$

$$\boxed{\frac{1}{2} = J_H = J_D}$$

Determination of Mass Transfer coefficient :-

The avg. mass flux can be calculated from

- the known area of the ~~wetted~~ wetted section of the ^{wall} area,
- & moisture content at the inlet and outlet of the column
- Avg. driving force, which the diff. b/w the pres of moisture in air & water.

*

$$k = \frac{\Delta m}{\Delta t \cdot A} \cdot \frac{P_A - P_{Ai}}$$

For diff^{fluids} at diff concentrations, at the diff t_{ms}, I can repeat the experiment. So that a co-relation can be generated.

Theories of Mass Transfer:-


Film Theory:-

It is given by Whitman in 1923, and it considers mass transfer from a solid to flowing liquid.

Assumptions:-

- 1> MT occurs purely by molecular diffusion at the phase boundary (wall.)
- 2> The M-T through the film occurs at steady state.
- 3> Bulk flow term will be negligible at the phase boundary, hence it is neglected.

After the film, the fluid is well mixed having the concentration which is the same as that of the bulk fluid concentration.
(C_{AB})



$$\frac{dN_A}{dz} = 0$$

$$N_A = N_{xA} + J_A$$

$$\frac{d(-D_{AB} \frac{dC_A}{dz})}{dz} = 0$$

$$-D_{AB} \frac{d^2 C_A}{dz^2} = 0$$

$$z=0, C_A = C_{Ai}$$

$$z=\delta, C_A = C_{Ab}$$

~~$$-D_{AB} \frac{dC_A}{dz}$$~~

~~$$-D_{AB} \frac{d^2 C_A}{dz^2} = 0$$~~

~~$$z = -D_{AB} C_A$$~~

$$\frac{d^2 C_A}{dz^2} = 0$$

$$\frac{dC_A}{dz} = C_1$$

$$dC_A = C_1 dz$$

$$C_A = C_1 z + C_2$$

$$C_A = C_{Ai} - (C_{Ai} - C_{Ab}) \frac{z}{\delta}$$

$$\frac{dC_A}{dz} = - \frac{(C_{Ai} - C_{Ab})}{\delta}$$

$$N_A|_{z=0} = -D_{AB} \frac{dC_A}{dz}$$

$$= -D_{AB} \left(- \frac{(C_{Ai} - C_{Ab})}{\delta} \right)$$

$$= \frac{D_{AB}}{\delta} (C_{Ai} - C_{Ab})$$

$$k = D_{AB}/\delta$$

$$k \propto D_{AB}$$

$$k \propto 1/\delta$$

Boundary layer thickness δ , kJ,

Profile of concentration — linear.

Penetration Theory:-

It is given by HIGBIE, Mass transfer from a rising bubble

As the bubble rises, liquid elements from the bulk reach the top of the bubble move along its periphery, reach its bottom, then get detached from it. and detached liquid elements eventually get mixed up with the bulk of liquid.

Assumptions:-

- 1) Unsteady state mass transfer occurs to a liquid elements as long as it is in contact with the bubble.
- 2) Equilibrium exist at the gas-liquid interface.
- 3) Each of the liquid element, stay in contact with the gas for the same period of time.

4)

$$\frac{\partial^2 C_A}{\partial x^2} = \frac{1}{D_{AB}} \frac{\partial C_A}{\partial t}$$

Initial Condition: $t = 0$

$$z \geq 0$$

$$C_A = C_{Ab}$$

Boundary Condition: $t \geq 0$
 $z = 0$

$$z = 0$$


$$C_A = C_{Ai}$$

$$z > 0$$

$$C_A = C_{Ab}$$



4) The liquid element will be of infinite thickness.



$$\frac{C_A - C_{Ab}}{C_{Ai} - C_{Ab}} = 1 - \text{erf } \eta$$

$$\eta = \frac{z}{2\sqrt{D_{AB}t}}$$

$$N_A|_{z=0} = \sqrt{\frac{D_{AB}}{\pi t}} (C_{Ai} - C_{Ab})$$

$$K = \sqrt{\frac{D_{AB}}{\pi t}}$$

instantaneous M-T coeff.

$$K_{Avg} = 2 \sqrt{\frac{D_{AB}}{\pi t_c}}$$

$$N_{Avg} = \frac{1}{t} \int_0^{t_c} N_A dt$$

July 16, 14

Surface Renewal Theory:-

It is given by DANCKWERT in 1951, The drawback of penetration theory is the assumption that the contact time is same for all the liquid element. In turbulent medium some of the liquid elements are swept away and some continue to be in contact for long time. There will be a distribution of age for the liquid elements present at the interphase at any moment.

Assumptions:-

- 1) Liquid element at the interphase are being randomly replaced by the fresh element from the bulk.
- 2) At any moment, each of the liquid elements at the surface has the same probability of being replaced.

$$K = \sqrt{D_{AB} \cdot S}$$

where S = fraction of surface area renewed in unit time.

Name	Founder	Assumptions	Dependence of k
Film Theory	Whitman 1923	MT occurs purely by molecular diffusion at phase boundary Steady state Bulk flow term is negligible	$k \propto D_{AB}$ $\propto 1/\delta$
Penetration Theory	Higbie	Unsteady state Equilibrium exist at gas-liq interphase. Contact time of each liq element with gas is same. Liquid element will be of infinite thickness.	

Raoult's Law :-

For an ideal gas liquid or vapour liquid system equilibrium relationship can be determine by Raoult's law

$$P_A^* = x_A P_A^v$$

P_A^* = equilibrium partial press. exerted by the solute

x_A = Mole fraction of the solute A in the liquid.

P_A^v = Vap. press of A at a given temp.

Henry's law:-

It gives the equilibrium data for non-ideal systems at low concentration.

$$P_A^* = \chi_A H$$

H = Henry's Constant
increases with increase in temp.

$$y_A^* = \chi_A m$$

$$P_A^* = C_A H'$$

Mass transfer between two phases:-

Mass transfer from one phase (say the gas phase G) to another phase (say the liquid phase L), involve following sequential step.

→ Solute A is transported from the bulk of the gas phase to gas liq. interphase bcz of some driving force say $(y_{Ab} - y_{Ai})$.

y_{Ab} = Mole fraction of A in gas bulk of gas.

y_{Ai} = " " " " on the gas-liquid interphase on the gas side.

Solute A is absorbed by the liquid phase at the gas liquid interphase such that the two concentrations are related by an equilibrium relationship.

$$y_{Ai} = \phi(\chi_{Ai})$$

or it is given by distribution coeff. k .

$$\text{where } k = \frac{y_{Ai}}{\chi_{Ai}}$$

$$\begin{array}{ccc} y_{Ai} \uparrow \chi_{Ai} & y_{Ai} \uparrow \chi_{Ai} & y_{Ai} \uparrow \chi_{Ai} \\ k > 1 & k = 1 & k < 1 \end{array}$$

The absorbed solute is transported from the gas-liquid interphase to the bulk of liquid bcz of some driving force which $(x_{Ai} - x_{Ab})$
 x_{Ai} = Mole fraction of A at the gas-liquid interphase on liquid side
 x_{Ab} = " " " " in the bulk of liquid.

$$\lim_{z \rightarrow 0^+} x_A = x_{Ai}$$

$$\lim_{z \rightarrow 0} y_A = y_{Ai}$$

The concept of interphase is totally hypothetical and has no practical significance. but we study it, to study the concept of mass transfer.


Determination of interfacial concentration:-

$$N_A = k_y (y_{Ab} - y_{Ai})$$
$$= k_x (x_{Ai} - x_{Ab})$$

Steady state
No accumulation
& no generation.

$$\frac{y_{Ab} - y_{Ai}}{x_{Ab} - x_{Ai}} = \frac{-k_x}{k_y}$$

 — slope of line




Since the concept of interface is hypothetical. Determination of interfacial concentrations accurately is impossible to solve this problem, we introduce the concept of overall mass transfer coefficient.

Overall M.T coeff. is analogous to overall H.T coeff. and for that overall driving force may be defined as based on the liquid side or based on the gas side.

$$N_A = K_y (y_{Ab} - y_{Ab}^*)$$

$$= K_L (x_{Ab}^* - x_{Ab})$$



K_y & K_L = Overall M.T coeff based on gas & liquid sides.

y_{Ab}^* = Concⁿ in a gas phase, which can remain in equilibrium with the bulk liq. phase concentration x_{Ab} .


x_{Ab}^* = Concⁿ in a liquid phase, which can remain in equilibrium with the bulk gas phase concentration y_{Ab} .

Determination of overall M.T coeff
gasside

$$y_{Ab} - y_{Ab}^* = (y_{Ab} - y_{Ai}) + (y_{Ai} - y_{Ab}^*)$$

$$\frac{N_A}{K_y} = \frac{N_A}{K_y} + \frac{N_A}{K_L}$$

$$\frac{1}{K_y} = \frac{1}{K_y} + m \frac{1}{K_L}$$



for liquids


$$(u_{Ab}^* - u_{Ab}) = (u_{Ab}^* - u_{Ai}) + (u_{Ai} - u_{Ab})$$

$$= \frac{(u_{Ab}^* - u_{Ai})}{(y_{Ab} - y_{Ai})} \times (y_{Ab} - y_{Ai}) + (u_{Ai} - u_{Ab})$$

$$\frac{N_A}{K_N} = \frac{N_A}{m'K_y} + \frac{N_A}{K_x}$$

$$\boxed{\frac{1}{K_N} = \frac{1}{m'K_y} + \frac{1}{K_x}}$$

July 17, 14

Distillation

Q. Why Reboiler partially evaporised the feed not totally?

Q. Do we always use a condenser (complete condensation)?

*Q. How much reflux is needed?

Q. How many types of feed are there & on which plate we introduce the feed?

Q. The total no. of trays required in a column are?

Q. General problem during the working of a distillation column.


Q. Why trays are used not packing?

Distillation is the technique of separation of more volatile component from the less volatile ones in a feed solution by partial vaporization of the feed followed by condensation.



In distillation, there are 4 parameters if (Temp., press, liq composition, vap. comp). if we fix any two of them then the system will be defined and in general we fix mainly temp & pressure. So that a data of $x-y$ can be generated.

$F = C - P + 2$
 $= 2 - 2 + 2 = 2$
 2 variables should be constant.
 DOF tells us the system is defined if DOF is zero then it is defined. If DOF is 1, then we should notice 1 variable should be constant.

T-xy diagram :-



$x \rightarrow$ A $\rightarrow$ increases
 B $\rightarrow$ decreases



How to draw my curve.

Suppose a fix temp. & composition of liquid is considered at G. It is heated and when the temp. reaches the pt M, it starts boiling. The composition of the first vapour so produced can be find out by the point N. Here MN is a tie line, which gives the equilibrium relationship between x & y . Clearly the more volatile component A is rich in the vapour phase i.e. $y > x$ which is the required condition for the distillation to take place. As the heating proceed the pt. N, ^{came} give when all the liquid is vapourised and last drop of the liquid is left. If we continue heating then the mixture shift into Superheated region and vice-versa. The set of x - y so generated can be plotted on the x - y curve, such that the equilibrium line always lie above the diagonal line at each and every pt.

Q.7 For a binary mixture of A & B, saturation temp are given
 $T_A = 49.2^\circ\text{C}$, $T_B = 80^\circ\text{C}$. The experiment is carried out at 70% & total pressure is 1 atm

$$\ln P = A' - \frac{B'}{C+T}$$

T.C
 P = mm of Hg.

$$A' = 15.8602$$

$$B' = 2589.2$$

$$C' = 231.36$$

for A component

$$A = 15.9037$$

$$B = 2789.01$$

$$C = 220.79$$

for B component

$$y_A = \frac{P_A}{P} = \frac{x_A P_A^v}{P}$$

Find the composition of more volatile in the vapor phase and the solution is ideal.

July 18, 14

Relative Volatility:-

Ease of separation of component A from component B or concentration ratio of A to B in the vapor phase to the same ratio in the liquid phase.

$$\alpha = \frac{(y_A/y_B)}{(x_A/x_B)} = \frac{\frac{y}{1-y}}{\frac{x}{1-x}} = \frac{y(1-x)}{x(1-y)}$$

$$y = \frac{\alpha x}{1 + (\alpha - 1)x}$$

$$\alpha = \frac{P_A^v}{P_B^v}$$

$$\frac{P_A/P}{P_B/P} = \frac{P_A/P_A^v}{P_B/P_B^v}$$



$$\alpha = \frac{\exp(A - \frac{B}{C+T})}{\exp(A' - \frac{B'}{C+T})}$$

Azeotrope:-

A solution which is highly ~~non~~ ideal often forms an azeotrope and azeotrope is defined as the mixture at which composition of more volatile is same to that in the liquid phase.

$$y^* = x$$


Minimum boiling Azeotrope :-





$$P = P_A + P_B$$

$$P = x_A p_A^v + (1 - x_A) p_B^v$$


Positive deviation :-



Maximum Boiling Azeotrope :-



Negative deviation :-



If the desired separation involve the crossing the azeotropic composition, It is generally not possible to separate components by normal distillation.

$$y = \frac{p_A}{p}$$


activity
coeff
for vapour
phase

$$\phi_A p y_A = x_A p_A^v \gamma_A$$

activity coeff for
liquid phase.

*** Batch Distillation :-

- ⇒ The feed is charged to a steel pot into which heat is supplied continuously through a steam jacket.
- ⇒ As the mixture boils, vapours which in more volatile component will form and as it continues concentration of more volatile in the liquid will decrease.
- ⇒ The vapour are led to a condenser and the condensate is collected in the drum.
- ⇒ At the begning, the condensate will be rich in the more volatiles. but as it continues concncentration of more volatile in the drum will decrease.
- ⇒ Condensate is usually withdrawn tym to tym having pcts of diff. concentration.



Mathematical
formulation

Let F be the no. of moles initially in the still pot. After the distillation begin, let at any moment no. of moles of liquid present in the still be L with a mole fraction of x . Let the moles of condensate will be D with a mole fraction of y^*

Material Balance

vaporizes so we use -ve sign

$$-dL = dD$$

not differentiating by fraction of more volatile

$$-d(Lx) = y^* dD$$

Component Balance

$$-L dx - x dL = y^* (-dL)$$

$$\frac{dx}{y^* - x} = \frac{dL}{L}$$

$$\int_F^W \frac{dL}{L} = \int_{x_F}^{x_W} \frac{dx}{y^* - x}$$

$$\ln \frac{F}{W} = \int_{x_W}^{x_F} \frac{dx}{y^* - x}$$

Rayleigh Eqn

vapour & liquid are in equilibrium

Solution of Rayleigh Eqn

$$y^* = \frac{\alpha x}{1 + (\alpha - 1)x}$$

$$\ln \frac{F}{W} = \int_{x_W}^{x_F} \frac{dx}{\frac{\alpha x}{1 + (\alpha - 1)x} - x} = \int_{x_W}^{x_F} \frac{dx}{x \left[\frac{\alpha - 1 - (\alpha - 1)x}{1 + (\alpha - 1)x} \right]}$$

$$= \int \frac{dx [1 + (\alpha - 1)x]}{x [\alpha - 1 - 2x + x]} = \int \frac{1 + (\alpha - 1)x dx}{x (\alpha - 1) (1 - x)}$$

$$= \int \frac{dx}{(\alpha - 1)x(1 - x)} + \int \frac{dx}{1 - x} = \frac{1}{\alpha - 1} \left[\frac{dx}{x} + \frac{dx}{(1 - x)} \right] + \frac{\ln(1 - x)}{-1}$$

$$= \left\{ \frac{1}{\alpha - 1} [\ln x - \ln |1 - x|] - \ln |1 - x| \right\} \Big|_{x_W}^{x_F}$$

$$\ln \left[\frac{F x_F}{W x_W} \right] = \alpha \ln \left[\frac{F(1 - x_F)}{W(1 - x_W)} \right]$$


for the question of batch distillation we can use only these 3 eqn first one is above

$$F = D + W$$

$$F x_F = D x_D + W x_W$$

valid only if α is constant

July 21, 14



Section above feed plate. i.e.


- Section below the feed plate more volatile component is stripped out of the liquid to get a relatively pure B at the bottom. Therefore it is named as stripping section.

★ The molecules of more volatile leaving the liquid phase absorb latent heat of vaporization. Also molecules of less volatile in the vapor phase condensed by release of latent heat of vaporization. By this process M.T takes place.

Enriching Section:-

* Counting of trays start from the top.

* Stages must have names of plates and they must be leaving



entering stream m-T still have to take place.
leaving stream are in equilibrium

Assumption

constant molar overflow (CMO), i.e. the no. of moles of more volatile vaporized is equal to no. of moles of less volatile condensed.

$$V_{n+1} = L_n + D$$

$$y_{n+1} = \frac{L}{V} x_n + \frac{D}{V} x_D$$

For Enriching Section

$$V_1 = V_2 = V_3 \dots = V_{n+1}$$

$$L_1 = L_2 = L_3 \dots = L_n$$

So sufficient no. drops from plates at wt from concentration

$$\frac{L}{V} x_n + \frac{D}{V} x_D$$

$$y_{n+1} = \frac{R}{R+1} x_n + \frac{x_D}{R+1}$$


$$R = \frac{L}{D} \text{ rectifying} = \frac{\text{Amt feed back}}{\text{Amt withdrawn}}$$

$$R+1 = \frac{L}{D} + 1 = \frac{L+D}{D} = \frac{V}{D}$$

$$x_n = x_D$$

$$y_{n+1} = x_D$$

Stripping Section:-



$$R = L'/D \text{ strip}$$

$$R = \frac{L'}{W}$$

$$R+1 = \frac{V'}{W} + 1 = \frac{V'+W}{W} = \frac{L'}{W}$$

$$L' = V' + W$$

$$L' x_m = V' y_{m+1} + W x_w$$

$$y_{m+1} = \frac{L'}{V'} x_m - \frac{W}{V'} x_w$$

$$= \frac{L'/W}{V'/W} x_m - \frac{W/W}{V'/W} x_w$$

$$R = \frac{V'}{W} = \frac{\text{Amt feed back}}{\text{Amt withdrawn}}$$

boil up ratio

$$y_{m+1} = \frac{R_v + 1}{R_v} x_m - \frac{x_w}{R_v}$$


for enriching section
 Slope of line $\frac{R}{R+1}$ where $R = L/D$
 Intercept of line $\frac{x_w}{R+1}$
 intersection pt (x_w, x_w)

pt (x_w, x_w) satisfies the line.

* $y_{m+1} = \frac{R_v + 1}{R_v} x_m - \frac{x_w}{R_v}$, slope $= \frac{R_v + 1}{R_v} \Rightarrow R_v = \frac{V'}{W}$, intercept $= \frac{x_w}{R_v}$
 x_w as x_w .

$\Rightarrow$ So again (x_w, x_w) satisfy the line. (intersection pt)

Feed Plate:-



q = fraction of feed i.e. in liquid.

$$V = \bar{V} + (1-q)F$$

$$\bar{L} = L + qF$$

$$\frac{V - \bar{V}}{F} = (1-q), \quad \frac{(\bar{L} - L)}{F} = q.$$

$$V = L + D \text{ (i)} \quad \text{---} \quad V y = L x + D x_D$$

$$L' = V' + W \text{ (ii)} \quad \text{---} \quad L' x = V' y + W x_W$$

adding (i) & (ii)

$$\frac{(V - \bar{V})y}{F} = \frac{(\bar{L} - L)x}{F} + \frac{D x_D + W x_W}{F}$$

$$(1-q)y = qx + x_F$$

$$y = \frac{-q}{1-q} x + \frac{u_F}{1-q}$$

Slope = $-\frac{q}{1-q}$, intercept = $\frac{u_F}{1-q}$ and intersection pt is (u_F, u_F) .

$$y = x$$


Defination of $-q$:-

q = heat required to change the feed from saturated liquid to saturated vapour
 $q = \frac{\text{molar latent heat of vaporization}}{\text{molar latent heat of vaporization}}$

Types of feed


Saturated liquid:-

$$q = 1$$




Partial liquid:-

$$0 < q < 1$$



Saturated Vapour



$$q = 0$$



(below sat temp)
Cold liquid:-

$$q > 1$$


Sensible + latent
 latent



Superheated Vapour

-ve (numerator)

$$q < 0$$



emitting section flashes
 as goodly.

July 23, 14

In general form.

$$A + B = C$$


$$\frac{A}{B} = \frac{n_B - \cancel{n_C}}{\cancel{n_C} - n_A}$$

$$\frac{C}{A} = \frac{n_A - \cancel{n_B}}{n_C - \cancel{n_B}}$$

$$\frac{B}{A} = \frac{\cancel{n_A} + n_C}{\cancel{n_C} - n_B}$$

$$\frac{B}{C} = \frac{n_C - \cancel{n_A}}{n_B - \cancel{n_A}}$$

q-lines :-




q -lines never intersect the equilibrium line bcz these happens only in ideal conditions

McCabe Thiele diagram:-

Assumptions.

- i) Constant Molar heat of vaporization & no. of moles of vapor condensed in the condenser is equal to the no. of moles of liquid vaporized in the reboiler.
- ii) Constant Molar overflow $\{V_1 = V_2 = V_3 = \dots = V_n\} \{L_1 = L_2 = L_3 = \dots = L_n\}$
- iii) No need to take energy balance bcz, no heat loss & gain are there.



last Δ should include the pt x_w in it, if triangle is just above the x_w then one more triangle should be formed. Or if the line is exactly on x_w then also we draw a triangle as we have to cross this pt

$$Eff = \frac{\text{actual no. of tray}}{\text{ideal no. of tray}}$$

➔ Mark the pts x_D, x_F & x_w on the diag.

➔ Calculate the intercept for the enriching line:

if McCabe Thiele ideal no. of tray is found.

- Join x_D with the intercept.
- Draw q -line based on the value of q and intersect this line with the enriching line and mark the pt as P.
- Join pt x_W with P, to get the stripping line.

total no. of tray N , and N including Reboiler.


Reboiler act as a tray, bcz separation of Vapour-liq takes place in the reboiler

Reboiler act as a pressure filler:-

Reboiler act as a pressure filler as it boils the liquids and changes its phase into vapour and increases the pressure.

Partial Condenser:-

then total no. of tray is
 $N-2$,




- Partial condenser is used, when the desired pdt is vapour.
- When there is difficulty to condense all of the vapour.


Total Reflux Ratio:-

- 1) The slope of enriching line is given by $\frac{R_{\infty}}{R_{\infty}+1} \simeq 1$, in the

Same way the slope of Stripping line is $\frac{R_v}{R_v+1} \simeq 1$.

This means that all the lines merges with diagonal line.





Total no. of trays required in this condition is minimum. therefore fixed cost decreases, but the duty of reboiler and condenser increases therefore operating cost increases.

Feed is once feed, afterwards $F=0$, $D=0$, $W=0$, then that condition is known as total reflux condition and it is denoted by R_{∞} .

Total reflux condition is used in the start-up of the plant to achieve the desired purity or to achieve equilibrium condition in the column.

Minimum Reflux Ratio: - (R_{min})

At the condition of minimum reflux ratio, the no. of trays required are maximum, therefore the fixed cost increases but the duty in this case is minimum and the operating cost decreases.

~~Optimum is 1.1 to 1.4~~

$$R_{opt} = 1.1 \text{ to } 1.4 R_{min}$$

Calculation of R_{min} :


The pt. of intersection of equilb q-line, enriching line and equilibrium line is noted and slope i.e. $\frac{R_{min}}{R_{min}+1}$ is calculated

$$by = \frac{x_D - y'}{x_D - x'}$$

$$\frac{R_{min}}{R_{min}+1} = \frac{x_D - y'}{x_D - x'}$$

$$R_{min} = \frac{x_D - y'}{y' - x'}$$

(x', y') - equilibrium pt.



R_{min} is more when intercept is less.

$$(y)_{\text{saturated liquid}} > (y)_{\text{saturated vapor}}$$

$$\left(\frac{x_D}{R_{min}+1} \right)_{SL} > \left(\frac{x_D}{R_{min}+1} \right)_{SV}$$

$$(R_{min})_{SL} < (R_{min})_{SV}$$

$$\Rightarrow x' = x_F$$

↓
Saturated liquid.


$$\Rightarrow x' > x_F \text{ or } x' < x_D$$

↓
Cold liquid.

$$\Rightarrow x' < x_F \Rightarrow \text{Partial liq.}$$


$$\Rightarrow y' = x_F \Rightarrow \text{Sat. Vap.}$$

$$\Rightarrow x' < x_W \Rightarrow \text{Superheated Vapor.}$$



$$(R_{min})_{q>1} < (R_{min})_{q=1} < (R_{min})_{0<q<1} < (R_{min})_{q=0} < (R_{min})_{q<0}$$

* Flash Vaporization :-



$$F = L + V$$

$$F x_F = L x + V y$$

$$F H_F + Q_F = L H_W + V H_D$$

Flash Vaporization is simply a stage in which rate of $V \& L$ is equal or we say


- In this operation, a liquid solution is partially vaporized to generate vapors which are allowed to establish equilibrium with the residual liquid.
- Enough time is given to the separator, such that the vapour and liquid streams come in equilibrium.
- Flash distillation is also known as ideal distillation or equilibrium distillation, or flash vaporization bec the liquid and the vapour streams are always in equilibrium.
- A flash distillation unit corresponds to an ideal tray in a Mc-Cabe Thiele diagram. Therefore a continuous distillation unit consisting of n ideal trays can be assumed as a network of n -flash distillation unit.
- For the case of flash distillation.

$$F = L + V$$

$$F x_F = L x + V y^* \quad \text{Component balance.}$$

$$F H_F + Q_H = L H_W + V H_D \quad \text{enthalpy of feed} \quad \text{enthalpy of distillate.}$$

Q_F = Heat duty given to the flash distillation unit.



July 25, 14

Underwood-Fenske Eqⁿ —

These are used to calculate min reflux ratio.

i) Feed is saturated vapour:—

$$q=0$$

$$R_{min} = \frac{1}{\alpha-1} \left[\alpha \frac{x_D}{x_F} - \frac{(1-x_D)}{(1-x_F)} \right] - 1$$

ii) Feed is saturated liquid:—

$$q=1$$

$$R_{min} = \frac{1}{\alpha-1} \left[\frac{x_D}{x_F} - \alpha \frac{(1-x_D)}{(1-x_F)} \right]$$

Fenske Eqⁿ :—


Fenske Eqⁿ for the calculation of minimum no. of ideal trays at the condition of total reflux.

$$N_m + 1 = \frac{\ln \left(\frac{x_D (1-x_W)}{x_W (1-x_D)} \right)}{\ln \alpha}$$

Reboiler.

Introduction of feed :—

In general for the vapour feed, we introduce the feed below the middle section (bottom). If the feed is more in liquid, we introduce it above the middle section (top). The actual location of feed plate be ~~don~~ determine by the McCabe Thiele diag. The triangle containing the pt x_F in the McCabe Thiele is the feed plate.



Entrainment :-

Liquid carried by vapour upto the tray above and it is caused by high vapour flow rate.

- i) It will contaminate the high purity distillate.
- ii) Excessive entrainment can lead to flooding.

Flooding :-

It is caused by the excessive vapour flow, causing liquid to be entrained in the vapour up the column, liquid cannot come down through the downcomer and also through the holes and ultimately distillation process stop. It is indicated by sharp increase in column pressure drop.

Weeping :-

It is caused by the low vapour flow rate. Pressure exerted by the vapour is insufficient to hold up the liquid on the tray. Therefore liquid starts to leave the hole. It is indicated by sharp decrease in column pressure.

Calculation of the column diameter :-

$$m = \rho A V$$

$$\boxed{\text{Molar flow Rate} = \frac{F}{M} A V} \rightarrow \frac{\pi}{4} d^2 - \text{downcomer}$$

A = Area of tray except diameter downcomer

$V =$ operating flooding Velocity:

July 28/14

Efficiencies in distillation:-

i) Overall Efficiency (η_o):-

(used for whole column)

Ratio of ideal no. of plates required by act.

or real no. of plate required.

ii) Murphree plate Efficiency (η_m):-

(used for plate)

$$\frac{\text{Actual mass transfer}}{\text{Ideal mass transfer}}$$


η_m can exceed 100% in some cases

iii) Point Efficiency (η_p):-




$$\frac{\text{Actual mass transfer}}{\text{Ideal mass transfer}}$$

Effect of Pressure on Distillation:-


1) As pressure increases Tray diagram shifts upwards and the width become narrower and vice versa



2) As pressure increases equilibrium line shift towards the diagonal line



When pressure decreases, the no. of plate required for the distillation also decrease.









4. In case of azeotrope, by decreasing the pressure azeotropic pt can be removed.



Therefore distillation column are always operated at low pressures.

- * Flash
- * Batch
- * McCabe
- * Fenske-Eqn


July 30, 14

Extraction

In absorption, we bring another phase (solvent) to gas phase & then the solute is absorbed in the solvent. For ex → to remove SO_2 we use water as solvent. The parameter is Solubility.

In distillation, liq & vap phase in form of feed are there containing two components A & B. No third component is added and the separation takes place bcz of diff. of relative volatility by the application of heat.

In Extraction, the feed is in the liquid phase containing (A+C) where the aim is to remove C, by the help of a solvent B. Also in the liquid phase and the parameter is solubility. In extraction, both the final prod names EXTRACT & RAFFINATE are in liq. phase and the separation is generally approached to equilibrium.



C is getting distributed in the two streams and the distribution can be found out by the help of distribution coeff.

$$K = \frac{y^*}{x} \rightarrow \begin{array}{l} \text{CH E} \text{ mole fraction of c in extract phase} \\ \text{C in R} \text{ mole fraction of c in raffinate phase} \end{array}$$


- ⇒ In Extraction, the mole fractions are used for the amount of c present in different streams.
- ⇒ B should be miscible with C but not with A or should be miscible with C & partially miscible with A.

Industrial Example: —

→ Acetic acid + water $\xrightarrow{\text{ethyl acetate (B)}}$ (C) (A)

- Pharmaceutical industry.
- Penicillin, vitamin-B-12
- Food industry in case of some juices.
- Petroleum industry for the case of lubricants and paraffins.

Equilateral triangular diagram:-




To find fraction if we have to find the fraction of A, B, C, draw a line parallel to that

To find concentration of any pt in the triangle.


→ Define the direction (either clockwise or anti-clockwise), define the direction in increasing way.

→ To find the concentration of any component, suppose C. Draw a line from a given pt parallel to AB and then find the concn of C from that extreme pt in which C ↑.

Stages:-



Two streams are brought in contact for sufficiently long time for mass transfer. We know that if long time is given, two ^{leaving} streams will be in equilibrium and the stage is known as ideal stage.



$$F+B=R+E \Rightarrow F+B=M=R+E$$

$$F x_F + B y_B = R x_R + E y_E \Rightarrow F x_F + B y_B = M x_M = R x_R + E y_E$$

$$M = R + E$$



$$\frac{R}{E} = \frac{x_E - x_M}{x_M - x_R}$$

$$\frac{M}{E} = \frac{x_E - x_R}{x_M - x_R}$$

$$\frac{M}{R} = \frac{x_R - x_E}{x_M - x_E}$$

Flowrate & Composition on Solute free basis
so we get str. line,

Cross-current stages or cascades



$x_0 = \frac{C}{A}$ mole fraction of C in carrier liq.

$$R_s x_0 + E_s y_0 = R_s x + E_s y$$

$$y = \left(\frac{-R_s}{E_s} \right) x + \left(\frac{R_s x_0 + E_s y_0}{E_s} \right)$$

$$R_s (x_0 - x_1) = E_s (y_1 - y_0)$$


$F = 1000 \text{ kg/hr}$
 $15\% \text{ C}$

$$R_s = 1000 - 150 = 850$$

Slope = -ive

$$= \left(\frac{\text{Raffinate}}{\text{Extract}} \right) \text{ Solute Free}$$

Crossing line has no equilibrium



Slope of line $= -R_s/E_s$ (-ve)

- from On the diagram, plot the points x_0 & y_0 such that x_0 is high y_0 low.
- Draw operating line with a slope of $-R_s/E_s$ such that it will hit the equilibrium curve (ideally).
- The pt. y_0 & x_2 mixes mixes on the 2nd stage, so we can draw the operating line with the slope same as such that it hit the equilibrium line again at x_2, y_2 and so on.
- If I know the extreme pts (x_1, y_1) & (x_0, y_0) , then by joining these 2, I can find the slope and from the slope data I can find the flowrate of solvent.

- If flowrate of solvent in each stage is changed then the slope at each point will change
- If we change the composition of the solvent, then the pts (N_0, Y_0) , (Y_0, X_1) , (Y_0, X_2) will not lie on a same line.

Q. An extraction process is going on to separate a feed mix (A+C) in which is $C = 15\%$ wt/wt & total feed flow rate is 1000 kg/hr . For extraction we are using a solvent B. (pure solvent - No C). Find the flow rate of the solvent required for the process such that C is removed by 95% .

- i) when single stage is used.
- ii) when 3 stages are used.

$$Y = 3.75 X$$


miss ratio.

(if capital letter, on the basis of solute free basis)

July 31, 14.

For Counter-Current:-

we prefer counter current more, as separation is more in this case



$$R_s(X_0 - X_3) = E_s(Y_1 - Y_4)$$


$$R_s X_0 - R_s X = E_s Y_1 - E_s Y_4$$

$$Y = \left(\frac{R_s}{E_s} \right) X + \frac{E_s Y_1 + R_s X_0}{E_s}$$

Slope for counter current cascade is true and is equal to

$$\frac{R_s}{E_s}$$

1
crossing line doesn't hit the equilibrium.



x_0, y_1
 x_1, y_2
 x_2, y_3

These are the pts
lie on operating
line.

x_1, y_1
 x_2, y_2
 x_3, y_3

These are the pts
lie on equilibrium
line.


Counter-current extraction is better than cross-current ext. bcz for the required separation we require less no. of stages.

→ Plot the pt. x_0, y_1 on the graph, from this pt draw an operating line with a slope of R_s/E_s .

→ We know that y_1 is in equilibrium with x_1 , so from the y_1 pt we can determine x_1 .

→ From the x_1 pt we can determine y_2 bcz x_1, y_2 lies on the operating line. and so on...



Types of System in Extraction:-




Type 1 :-

One pair is partially soluble

$A+B+C \rightarrow$ form a binary system in which $A+B$ partial miscible, $B+C$ comp. miscible, $A+C$ completely miscible.



If we take any pt in the phase diagram and allow it to separate, then we get 2 phases one is rich in B known as extract phase and other is rich in A known as Raffinate, so both the phases contain A, B, C & all.



Outside this region every pt represent homogeneous solution of $A+B+C$ which is not separated.

Any pt inside the phase diagram on the line AB, they also get separated into components.

The line RE is known as a tie line and it represents one stage. For multi-stage cascade and there will be more than one tie line and they may or may not be parallel.



Plait Point:-

Plait point is a point upto which we can separate the mixture but which extraction is not possible. It is also defined as that pt. at which slope change and starts decreasing.

Temperature effect on Type I System

As temp $\uparrow$ and phase diagram shrinks

As " " ,]

" " $\uparrow$, Area of partial miscibility decreases.





and a stage may come at which phase diagram vanishes and we have a complete mixture.

At this pt. Separation is impossible $\therefore$ Extraction is termed

out ~~at~~ generally at room or low temp.

Type 2:-


System of $A+B+C$, two pairs are partially miscible
 $A+C$ completely soluble, $A&B$ partially soluble.
 $B&C$ partially soluble.




The phase diagram hitting the lines AB & BC bcz these 2 pairs are partial miscible, any pt outside this phase diagram represents a homogenous mixture and can't be separated. Any pt inside this region or either lies on line on inside Δ will get separated.

In Type-2 System amount of solute present in raffinate phase is more ^{than} present in the extract phase which is just opposite to the process of extraction.


By increasing the temp, solubility will increase and the solubility depend of solvent choose. Solvent B is taken such that solubility of $B&C$ increasing by increasing the temp and type 2 system converted into Type-1 system.



Multistage Stage Cross-current Extraction: -




Each stage consist of a network of mixer and settler and represents an ideal stage. Streams $R_1, E_1, R_2, E_2, R_3, E_3$ are in equilibrium and the solvent entering in each stage have the same flow rate and same composition.



If we change the composition of the solvent in diff. stages when the pt b, will towards the b. If we change the flow rate of solvent in different stages then M_1, M_2, M_3 will change.

If amt of solvent ↑, then the mixture point will shift towards B and vice-versa.

Aug 01, 14


Minimum amt of solvent required for extraction:-

$$\frac{F}{B} = \frac{y_s - x_M}{x_M - x_F}$$

$$\left(\frac{F}{B}\right)_{\min} = \frac{y_s - x_D}{x_D - x_F}$$

In the Δ phase diag. we can find the feed and the solvent to form a mixture M in the mixture which can then be separated in the separator by the help of a tie line shown in the diagram.

$$F + B = M$$



If the amount of solvent is decreased then the point M will shift towards F on the feed line.

The question is how much we can decrease the amount of solvent such that extraction will take place.

The answer is given by the equilibrium line as we know that at any stage we can't cross the equilibrium line.

When the feed line intersects the equilibrium line at pt D. That point represents the pinch point and also the last point upto which extraction can take place. The minm amt of solvent used at this stage can be find out by the mixing rule.

$$\left(\frac{F}{B}\right)_{\min} = \frac{y_s - x_D}{x_D - x_F}$$


And at this pt, a very small amt of extract will form and this line DD' represent the upper limit of extraction like in the distillation column when we heat a mixture, the pt at which 1st vapour is formed is the limit of distillation.

Increasing amount of Solvent:—



In the previous diagram, if we increase the amount of solvent, then the pt M will shift towards the B on the feed line and the limit is again given the equilibrium curve at the pt. F' . Such upto which extraction have minimum. This line FF' shows the upper limit of extraction like in the distillation column, if we heat a mixture a tym comes when last drop of liquid is left. The max^m amt of solvent at this point can be find out by the mixing rule.

$$\left(\frac{F}{B}\right)_{\max} = \frac{y_s - x_G}{x_G - x_F}$$

X




Extraction



Distillation

When the mixture is at D in the separator, it stays at the same concentration as D and a drop of liquid goes out as the ~~extract~~ like in distillation, initial vapour forms. When the mixture is at G , it stays at the same composition as the pt G and the drop of raffinate goes out like in distillation last drop of liquid left.

Multi-stage Counter Current Extraction:-



$$F + S = R_3 + E_1 \quad \text{overall M.B.}$$

$$F - E_1 = R_3 - S$$

$$R_1 + S = E_2 + R_3$$

$$R_1 - E_2 = R_3 - S$$

$$F - E_1 = \Delta$$

$$R_1 - E_2 = \Delta$$


$$R_2 - E_3 = \Delta$$

$$F - S = M$$

$$M \quad F \quad S$$

$$F + S = M$$

$$F \quad M \quad S$$




The value of reduction ratio for cross-current extraction.

$$-\frac{A}{B} = \frac{Y_n - Y_s}{X_n - X_{n-1}}$$

$Y_s = 0$ (solute free/solvent pure)

$Y = mx$ (equilibrium line st.)



$$-\frac{A}{B} = \frac{m X_n}{X_n - X_{n-1}}$$

$$1 + \frac{mB}{A} = \frac{X_{n-1} - X_n}{X_n} + 1 = \frac{X_{n-1} - X_n + X_n}{X_n}$$

$$\boxed{1 + \frac{mB}{A} = \frac{X_{n-1}}{X_n}}$$

for n^{th} stage.

if $n \geq 1$ $1 + \frac{mB}{A} = \frac{X_F}{X_1}$

$n \geq 2$ $1 + \frac{mB}{A} = \frac{X_1}{X_2}$

$$\frac{X_F}{X_n} = \frac{X_F}{X_1} \times \frac{X_1}{X_2} \times \frac{X_2}{X_3} \times \dots \times \frac{X_{n-1}}{X_n}$$

$$= (1 + \frac{mB}{A}) \cdot (1 + \frac{mB}{A}) \cdot \dots \cdot (1 + \frac{mB}{A})^n$$


$$= (1 + \frac{mB}{A})^N$$

$$\boxed{\frac{X_F}{X_n} = (1 + \frac{mB}{A})^N}$$

$$\Leftarrow = \left(1 + \frac{m E_s}{R_s}\right)^N$$

$$\boxed{NB = \frac{AN}{m} \left[\left(\frac{X_F}{X_n}\right)^{1/N} - 1 \right]}$$

$\Leftarrow$



Reduction Ratio formula for counter current ~~ratio~~ system

$$\frac{X_F}{X_n} = \frac{\left(\frac{mB}{A}\right)^{N+1} - \left(\frac{mB}{A}\right)^N}{\left(\frac{mB}{A}\right)^{N+1} - 1}$$

Aug 04, 14

Drying

The removal of moisture from a wet solid, solution solid or a gas to make it dry is known as drying.


Drying not always demands complete removal of moisture
for ex $\rightarrow$ moisture is not removed completely in the drying of a soap bar.

Generally the final prod in drying is a solid but not always.

Drying is best example of Simultaneous H.T & M.T.

Physical Mechanism of Drying:-

Generally a moist solid is heated to vaporize the moisture to the surface and then heat required for drying is supplied by hot air.

Mechanism of moisture transport1) By liquid diffusion:-

The concn of the moisture inside the bulk of solid is generally more than the moisture content present at the surface. Bcz of this concentration diff. the moisture will flow from inside to the surface.

2) By Capillary Process:- forces:-

Generally in porous solids, moisture transport occurs due to capillary forces. (when pores are in the form of capillary).

3) Pressure induced transport

For solids, which shrink during drying. Outer layer shrinks and compress the inside moisture to come to the surface.

4) Vapour Diffusion:-

Sometimes liquid Vapourises inside the surface of solid and these vapours come to the surface known as vapour diffusion.

Resistances in drying:-

- 1) Resistance to liquid and vapour diffusion from inside to the surface. (top of solid)
- 2) Resistance to convective M.T of the vapour from surface of solid to the bulk of Air ^{lgs}
- 3) Resistance to convective H.T from Bulk of drying air to the solid surface.
- 4) Conductive H.T resistance due to increased temp, of the outer layer of solid to inside

Bone Drying:-

A solid totally free from moisture is known as bone dry

Case hardening:-

Sometimes in drying of a soap bar, the ^{drying} action is so rapid that the outer layer becomes stiff and hard and stops drying, but inside the surface of solid there is enough amt of moisture present this is known as case hardening.

Type of moisture

Unbound Moisture:-

Moisture content present over the surface of solid such that no resistance is offered by the solid in the movement of this moisture or the moisture content whose relative humidity is 1 is known as unbound moisture. ^{path of drying instant} ^{during the removal of} ~~unbound moisture.~~
moisture content which is in equilibrium with 100% humidity

Bound Moisture:-

Moisture content present inside the surface of solid such that its relative humidity is less than 1 or solid is

Offering resistance in the movement of moisture is known as bound moisture.


Free Moisture:-

or which is desired to remove


The moisture content which can be removed from the solid either bound or unbound is known as free moisture.

Equilibrium Moisture Content:-


The moisture content at which the dry stops and the V.P of moisture over the solid is eq becomes equal to the partial pressure of water vapour present inside the air. Rate of drying becomes zero. It's not constant, bt depends on the temp, humidity & nature of solid. Bt for the given condition of solid & dry air it is constant.



Variation of Moisture content with t_m:-



Rate of drying vs Moisture Content



Rate of drying

$$N = -\frac{W_s}{A} \frac{dx}{dt}$$

$$x \rightarrow \frac{\text{kg moisture}}{\text{kg wet solid}}$$

$$X = \frac{x}{1-x}$$

N = Rate of drying

A = Area of drying

W_s = Wt. of bone dry

x = Moisture content (kg moisture/kg dry solid)

T = time

* In quest, we always assume concn of dry basis until unless it is not mentioned.

Type of drying:-

$$\int dt = -\frac{W_s}{A} \int_{x_i}^{x_f} \frac{dx}{N}$$

$$t = \frac{W_s}{A} \left[\int_{x_c}^{x_i} \frac{dx}{N_c} + \int_{x_f}^{x_c} \frac{dx}{N} \right]$$

$$t = \frac{W_s}{A N_c} (x_i - x_c) + \frac{W_s}{A} \int_{x_f}^{x_c} \frac{dx}{N}$$

$$t = \frac{W_s}{A N_c} (x_i - x_c) + \frac{W_s}{A} \int_{x_f}^{x_c} \frac{dx}{p x + q}$$

$$t = \frac{W_s}{A N_c} (x_i - x_c) + \frac{W_s}{P A} \ln \frac{P x_c + q}{P x_f + q}$$

$$+ \frac{W_s}{P A} \ln \frac{P x_c - P x^*}{P x_f - P x^*}$$

$$+ \frac{W_s}{P A} \ln \left| \frac{x_c - x^*}{x_f - x^*} \right|$$

Assumption
drying rate is linear.

$$N = p x + q$$

$$N_c = p x_c + q$$

$$p x_c - p x^* = N_c$$

$$p(x_c - x^*) = N_c$$

$$\frac{1}{p} = \frac{x_c - x^*}{N_c}$$

$$0 = p x^* + q$$

$$N_f = p x_f + q$$

$$0 = p x^* + q$$

$\frac{W_s}{P A}$
comes from
diff. of
integrating

$$t = \frac{W_s}{A N_c} (x_i - x_c) + \frac{W_s}{A N_c} (x_c - x^*) \ln \frac{x_c - x^*}{x_f - x^*}$$

$x_f \neq x^*$
if it is go for
proper integration
don't use this
formula.

$$t = t_c + t_v$$

const. dryⁿ variable
type dryⁿ type

$$\frac{t}{x^*} \quad \frac{t}{x_c} \quad \frac{t}{x_i}$$


$$t = \frac{W_s}{A N_c} \left[(x_i - x_c) + (x_c - x^*) \ln \left| \frac{x_c - x^*}{x_f - x^*} \right| \right]$$

$X =$ kg of moisture / kg of dry solid.
↓
Dry Basis

$x =$ kg of moisture / kg of wet solid
↓
Wet basis

$$X = \frac{x}{1-x}$$

Aug 05, 14



Constant Rate of drying Period :-

Humidity / Sp. humidity / Absolute humidity (H) :-

Amount in kg of vapour present in air
kg of dry air.

$$H = \frac{m_v}{m_a} \text{ — Vapour} \text{ — air}$$

$$P_v V_v = m_v R_v T_v$$

$$P_a V_a = m_a R_a T_a$$

If vapour behaves as ideal gas
then only we apply
dry gas behaves as ideal gas

→ Vapour & air are in thermal equilibrium

$$T_a = T_v$$

D

$$V_a = V_v$$

P_v = Part. press of water vapour in air
 P = total press.

for general system.

$$\frac{P_v}{P_a} = \frac{m_v}{m_a} \frac{P_v}{P_a} = \frac{m_v}{m_a} \cdot \frac{P_v}{P - P_v}$$

$$H = \frac{m_v}{m_a} = \frac{P_v}{P_a} \times \frac{R_a}{R_v}$$

$$0.287 \text{ kJ/kg K}$$

$$R_a = R/M_a = \frac{8.314}{28.916}$$

$$R_v = R/M_v = \frac{8.314}{18}$$


$$0.462 \text{ kJ/kg K}$$

for air-water system.

$$H = 0.621 \frac{P_v}{P_a}$$

$$H = 0.621 \frac{P_v}{P - P_v}$$

P_a = dry air never exist
 $\therefore$ pressure exerted by dry never be calculated.



$$Q = hA(T - T_w)$$

$$N_A = k_y(y_w - y)$$

$$H = \frac{P_v}{P - P_v} \times \frac{M_v}{M_a} \frac{M_v}{M_a}$$

$$P \gg P_v$$

for dry gas

$$H = \frac{P_v}{P} \times \frac{M_v}{M_a} = y \frac{M_v}{M_a}$$

$$H_w = y_w \times \frac{M_v}{M_a}$$

for near the moister

$$N_A = k_y \frac{M_a}{M_v} (H_w - H)$$

$$Q = \frac{\overset{\text{Mass}}{M_v \cdot N_A}}{\underset{\text{Kg mol}^{-1}}{\text{m}^2 \text{s}}} \times \lambda \cdot \overset{\text{Area}}{A}$$

total amt of heat required to vapourise unbound moisture

Amt. of heat necessary to vapourise N_A amount of water in terms of latent heat of vapourization is given by

$$Q = M_v N_A \lambda A$$

$$h A (T - T_w) = M_v \{k_y (y_w - y)\} \lambda A$$

$$\boxed{\frac{h(T - T_w)}{\lambda} = k_y M_a (H_w - H)} = N_c$$

↓
Imp.

→ Unbound

Assumptions:-

- H.T by radiation & conduction to the solid surface are neglected.
- It has been found that the more reliable method to calculate the constant rate of drying period is temp diff. in comparison to humidity difference bcz the temp diff can be measured more accurately with less errors in comparison to humidity diff.

Aug 06, 14

Effects of variables on Drying:-

1) When air flowing parallel to the surface

h.T coeff. $\rightarrow h = 0.0204 G^{0.8}$

2) When air is flowing $\perp$ to the surface

$$h = 1.17 G^{0.37}$$

sv mass velocity
 $\frac{\text{kg} \cdot \text{m}}{\text{m}^2 \cdot \text{s}}$

3) As air velocity increase, rate of drying increase by an amount

$$N_c \propto V^{0.8}$$

$$N_c \propto V^{0.37}$$

4) As gas humidity increase, rate of drying decreases.

5) As gas temperature increases, rate of drying increases.

6) As thickness of solid increases, rate of drying remains same under constant drying rate. But under falling drying rate, rate of drying will decrease.

7) As thickness increases, T_c remains the same but T_v increases.


Relative humidity

Ratio of partial pressure of vapour in air to the v.p of moisture.



Absorption


Co-current Contacting Equipment:-




$$R_s(x_1 - x) = E_s(Y - Y_1)$$

$$R_s(x_1 - x_2) = E_s(Y_2 - Y_1)$$

$$Y = -\frac{R_s}{E_s} X + \frac{(R_s X_1 + E_s Y_1)}{E_s}$$



Counter Current Contacting Equipment:-




$$X_2 > X_1, Y_2 > Y_1$$

$$R_s(x_1 - x) = E_s(Y_1 - Y)$$

$$Y = \frac{R_s}{E_s} X + \left(\frac{E_s Y_1 - R_s X_1}{E_s} \right)$$


$$Y = mX + C$$



» Slope is +ve

» Gives more separation, than cross-current


Absorption



A gas containing two components A & C, in which the component C is undesirable like H_2S , SO_2 , NO_x in air. To separate the Component C in the gas phase, we are using solvent like H_2O , KOH , ethanol etc which absorbs the solute C. The gas phase and the liquid phase enter counter-currently and the desired removal of C from the gas phase is achieved by adjusting the following parameters.

- Solvent Flow Rate
- Height of column
- Gas flow rate
- Diameter of the column

Solvent Flow Rate




$$G_{NS} Y_1 + L_S X_2 = L_S X_1 + G_{NS} Y_2$$

$$G_{NS} (Y_1 - Y_2) = L_S (X_1 - X_2)$$

$$Y = \frac{L_S}{G_{NS}} X + \frac{G_{NS} Y_1 - L_S X_1}{G_{NS}}$$

$$Y = \frac{L_S}{G_{NS}} X + \frac{G_{NS} Y_2 - L_S X_2}{G_{NS}}$$

Drop the suffix of X_2, Y_2 as we know the value of X_2, Y_2 .



$X > Y$

$$\left(\frac{L_S}{G_{NS}}\right)_{1.5} = \left(\frac{L_S}{G_{NS}}\right)_{opt.}$$

- ⇒ Plot the points X_2, Y_2 , such that applies above the equilibrium line.
- ⇒ Plot the point Y_1 , and extend it to hit equilibrium top.
- ⇒ From the pt X_2, Y_2 , Draw a line to intersect the point of intersection of equilibrium line and Y_1 . That point will give X_1^* (Maximum achievable concentration)
- ⇒ This line as a slope of $(L_S/G_{NS})_{min}$ and from the literature if we multiply by 1.5, we will find $(L_S/G_{NS})_{opt.}$
- ⇒ From the pt X_2, Y_2 . Draw another line with a slope of $(L_S/G_{NS})_{opt.}$ operating/optimum upto the pt where it hits the line Y_1

→ The pt of intersection of γ_1 will give us x_1

$$L_s(x_1 - x_2) = G_s(\gamma_1 - \gamma_2)$$



$$\gamma_2 = f(x)$$

$$\gamma_1 = f(x_1^*)$$

$$L_{s_{\min}}(x_1^* - x_2) \geq G_s(\gamma_1 - \gamma_2)$$


$$L_{s_{\text{opt}}} = 1.5 L_{s_{\min}}$$

For stripping



$$(L_s)_{\min} \times 1.5 = (G_s)_{\text{opt}}$$

Aug 07, 14

Height of Absorption Column

$$Z = NTU \times HTU$$

HTU (Height of Transfer Unit)

Overall HTU is defined as the height of pack section required to accomplish a change in the concentration equal to that avg. driving force in that section.

$$-d(Gy) = d(Lx) = \text{Rate of M.T.}$$

$$G_s = G(1-y)$$

$$-d\left(G_s \frac{y}{1-y}\right)$$

$$G_s \left[\frac{(1-y) \cdot dy - y(-dy)}{(1-y)^2} \right] = -G_s dy \left(\frac{1}{(1-y)^2} \right)$$

$$= -\left(\frac{G}{1-y} \right) dy$$

$$\frac{G_s}{A} = \frac{G}{A} - \frac{G_y}{A} = \frac{G}{A} - \frac{G y}{A}$$

$$L_s = L(1-x)$$

$$-d\left(L_s \frac{x}{1-x}\right)$$

$$-L_s d\left(\frac{x}{1-x}\right)$$

$$-L_s \left[\frac{(1-x) dx - x(-dx)}{(1-x)^2} \right] = -L_s dx$$

$$= \frac{L}{1-x} dx$$

Chapman
&
Solomon

Interfacial area.

$$k_y(y-y_i) \leftarrow N_A \cdot a \left(\frac{m^2}{m^2 s} \right) A_T dz = - \frac{G}{1-y} dy$$

$\downarrow$
 $\frac{\text{kmol}}{m^2 s}$

$$dz = - \frac{G}{1-y} \frac{dy}{k_y(y-y_i) a A_T}$$

$$\int_{y_2}^{y_1} dz = - \int_{y_2}^{y_1} \frac{G}{1-y} \frac{dy}{k_y(y-y_i) a A_T}$$

$$Z = \int_{y_2}^{y_1} \left(\frac{G'}{A_T a k_y(y-y_i)(1-y)} \right) \times \frac{(1-y)_{LM}}{(1-y)_{LM}}$$

This quantity found exp. const

$$= \int_{y_2}^{y_1} \left(\frac{G'}{k_y(1-y)_{LM} a} \right) \times \frac{dy(1-y)_{LM}}{(y-y_i)(1-y)_L}$$

$(1-y)_{LM} = \frac{(1-y_i) - (1-y)}{\ln \frac{1-y_i}{1-y}}$

to simplify the integration as const factors taken out of $\int$.

$$Z = \underbrace{\frac{G'}{k_y(1-y)_{LM} a}}_{HTU} \int_{y_2}^{y_1} \underbrace{\frac{dy(1-y)_{LM}}{(y-y_i)(1-y)}}_{NTU}$$

for dilute solution:-

$$(1-y)_{AM} = \frac{(1-y_i) + (1-y)}{2} \approx 1$$

$$Z = \underbrace{\frac{G'}{k_y a}}_{HTG} \int_{y_2}^{y_1} \underbrace{\frac{dy}{(y-y_i)}}_{NTG}$$

$\frac{\text{kmol}}{m^2 s}$

$\Rightarrow HTG = \frac{G'}{k_y a}$

k_y = Individual M.T coeff based on gas side.

$$H_{TOG} = \frac{G'}{K_y a}$$

— K_y = Overall M-T coeff. based on gas side.

H_{TG} :- Height of transfer unit based on ^{individual} M-T coeff on the gas side.

H_{TOG} :- Height of transfer unit based on overall M-T coeff on the gas side.

$$H_{TL} = \frac{L'}{K_x a}$$

H_{TL} :- Height of transfer unit based on individual M-T coeff on liquid side.

$$H_{TOL} = \frac{L'}{K_2 a}$$

H_{TOL} :- Height of transfer unit based on overall M-T coeff on the liquid side.

$$N_{TG} = \int_{y_2}^{y_1} \frac{dy}{y - y_i}$$

N_{TG} :- No. of transfer unit based on interfacial concentration on gas side.

No. of transfer unit based on individual transfer unit

$$N_{TOG} = \int_{y_2}^{y_1} \frac{dy}{y - y^*} = N_{TG} = N_{TOG} (y - y^*)$$

N_{TOG} :- No. of transfer unit based on equilibrium concentration on gas side.

$$N_{TL} = \int_{x_2}^{x_1} \frac{dx}{x_i - x}$$

as $\frac{d(x)}{x - x_i}$ check

N_{TL} :- No. of transfer unit based on interfacial concⁿ on the liq. side.
 $N_{TL} = N_{TOL} (x^* - x)$



$$N_{TOL} = \int_{x_2}^{x_1} \frac{dx}{x^* - x}$$

N_{Ta} :- No. of transfer unit based on overall composition on the liq. side.


Re:

$$Z = N_{Ta} \times H_{Ta} = N_{TL} \times H_{TL} = N_{TOG} \times H_{TOG} = N_{TOL} \times H_{TOL}$$

**
 $y > y_i > y^*$
 $x^* > x_i > x$



$$\frac{y - y_i}{x_i - x} = \frac{-k_x}{k_y}$$



In terms of gas.

$$NTU = \frac{y_{n+1} - y_1}{y_1 - y^*}$$

min

In terms of
Vapour.

$$NTU = \frac{X_n - X_0}{\frac{X^* - X_0}{m}}$$

Solute free or not =

Aug 08, 14

$$NTU = \int_{y_2}^{y_1} \frac{dy}{y - y^*}$$

If the equilibrium lines and operating lines are st. and parallel then the no. of transfer unit based on gas phase can be calculated by,

$$NTOG = \ln \left[\frac{\left(\frac{y_1 - mx_2}{y_2 - mx_2} \right) (1 - \frac{1}{A}) + A}{1 - \frac{1}{A}} \right]$$

$$y_1 \approx y_{n+1} \quad x_2 \approx x_0$$

$$y_2 \approx y_1$$

$$NTOG = \ln \left[\frac{\left(\frac{y_{n+1} - mx_0}{y_1 - mx_0} \right) (1 - \frac{1}{A}) + A}{1 - \frac{1}{A}} \right]$$

A = Absorption factor and is defined by the slope of operating line to the slope of equilibrium line.

$$A = \frac{L/G}{m} = \frac{L_S/G_S}{m}$$

* A = 1 no. of stages = no. of transfer units.

$$N_p = \frac{y_{n+1} - y_1}{y_1 - mx_0}$$

$$NTU = N_p$$

$$HTU = HETP$$

In case of stripping:-

$$NTOL = \ln \left[\frac{\left(\frac{x_2 - y_1/m}{x_1 - y_1/m} \right) (1 - A) + A}{1 - A} \right]$$

$1/A$ = stripping factor,

$$1/A = \frac{m}{L/G}$$

For calculation of theoretical no. of ideal trays we can use
~~Carnel~~ ^{Kramers} eqn

no. of trays
not stages.

$$N_p = \frac{\ln \left[\left(\frac{y_1 - mx_2}{y_2 - mx_2} \right) (1 - 1/A) + 1/A \right]}{\ln A}$$



$$N_{TOL} = \frac{\ln \left[\left(\frac{x_2 - y_1/m}{x_1 - y_1/m} \right) (1 - A) + A \right]}{\ln 1/A}$$

HETP :- (Height equivalent to theoretical plate) :-

It is defined as the height of packed section required to accomplish a change in concentration equal to M.T takes place on a plate.

HETP (in terms of H_{TOG}) :-

~~$$HETP = \frac{H_{TOG} \ln(1/A)}{(1 - 1/A)}$$~~

$$HETP = H_{TOG} \frac{A \ln A}{A - 1}$$

$$A = \frac{L/G}{m}$$

Relⁿ b/w N_{TOG} & N_{TP} :-

$$N_{TOG} = \frac{N_p \ln A}{(1 - 1/A)}$$

N_p = no. of theoretical plates

Efficiency in a packed column :-

Point Efficiency :-

It is defined by $\frac{\text{Actual M.T on any pt in a packed coln}}{\text{Ideal M.T.}}$

It is given by

$$E_{OG} = 1 - e^{-N_{TOG}}$$

Murphree plate Efficiency

$\frac{\text{Actual M-T on a plate}}{\text{ideal M-T on a plate}}$

$$E_{MG} = \frac{y_{n+1} - y_n}{y_{n+1} - y_n^*}$$

check whether it is capital or not



Overall tray Efficiency / Column Efficiency :-

assumes
equilibrium line &
operating line both
are straight

$$= \frac{\text{No. of ideal trays}}{\text{No. of real trays}}$$

$$E_O = \frac{\ln \left[1 + E_{MG} \left(\frac{m}{L/G} - 1 \right) \right]}{\ln \left(\frac{m}{L/G} \right)}$$

→ Gilliland Equation

if $A \neq 1$

$$E_O = E_{MG}$$

Relation b/w H_{TOG} in term $H_{TCG} \times N_{TL}$:-

$$\frac{1}{K_y a} = \frac{1}{K_y a} + \frac{m}{K_x a}$$

$$\frac{H_{TOG}}{G'} = \frac{H_{TCG}}{G'} + m \frac{H_{TL}}{L}$$

$$H_{TOG} = H_{TCG} + m \frac{H_{TL}}{L} G'$$

$$H_{TOG} = H_{TCG} + \left(\frac{1}{A} H_{TL} \right)$$

$$H_{TOG} = \frac{G'}{K_y a} ; H_{TCG} = \frac{G'}{K_y a} , H_{TL} = \frac{L'}{K_x a} , H_{TO2} = \frac{L'}{K_x a}$$

Relation between

$$\frac{1}{K_a a} = \frac{1}{k_a a} + \frac{1}{m k_y a}$$

$$\frac{H_{TOL}}{L'} = \frac{H_{TL}}{L'} + \frac{H_{TQ}}{m L'}$$


$$H_{TOL} = H_{TL} + A H_{TQ}$$

One more formula for NTU, when $1/s_1, s_2$ are not given only composition are given.
 $\Rightarrow$ equilibrium curve must be ϕ .

$$= \frac{y_1 - y_2}{(y - y^*)_{LM}}$$

$$(y - y^*)_{LM} = \frac{(y_1 - y_1^*) - (y_2 - y_2^*)}{\ln \frac{y_1 - y_1^*}{y_2 - y_2^*}}$$

In absorption



$$\begin{aligned} y &> y_1 > y^* \\ x^* &> x_1 > x \end{aligned}$$

Aug 11, 14

Humidity

This term is used to integrate the concentration of vapour in a gas-vapour mixture. It can be defined on mass basis or mole-basis.

$$\text{mass basis } H = \frac{m_A}{m_B} = \frac{P_v}{P - P_v} \cdot \frac{M_v}{M_a} \quad \left| \quad H = 0.622 \frac{P_v}{P - P_v} \right| \text{ for air-water system.}$$

$$\text{mole basis } H' = \frac{n_A}{n_B} = \frac{P_v}{P - P_v}$$

$$H = H' \frac{M_v}{M_a}$$

$$H = 0.622 H'$$

If the gas were saturated with vapour.

* At saturation partial press of water vapour = Vapor pressure of water at same temp.
 $P_v = P_s$

Molar humidity at saturation

$$H_s' = \frac{P_s}{P - P_s} = \frac{n_v}{n_a}$$

$$H_s = 0.622 H_s'$$

Mass humidity at saturation

$$H_s = \frac{P_v}{P - P_v}$$

% Saturation or degree of saturation (μ) =

defined as ratio of kg of vapour present in given mass of air at given dry bulb temp (DBT) for same ratio at saturation.

$$\mu = \frac{H}{H_s} = \frac{H'}{H_s'}$$

$$\mu = \frac{h}{h_s} = \frac{\frac{P_v}{P - P_v}}{\frac{P_s}{P - P_s}}$$

$$= \frac{P_v}{P_s} \times \frac{P - P_s}{P - P_v}$$

Relative humidity :- (ϕ)

It is given by the ratio of partial pressure of water vapour to the vapour pressure. At saturation $\phi = 1$

$$\phi = \frac{P_v}{P_s}$$

* $\phi = 1$ when $P_v = P_s$




$$\phi = \frac{\mu}{\left[1 - (1 - \mu) \frac{P_s}{P}\right]}$$

Dry bulb temp :- (True temp)

The temp. recorded by a thermometer whose bulb is perfectly dry and is not affected by the presence of any moisture content present in the atmosphere and also not by any radiations present in the surrounding.

Wet bulb temp :-



The temp. recorded by the thermometer whose bulb is covered with a ~~wetted~~ ^{wetted} muslin wick and more pass the unsaturated air with a velocity of 2-5 m/sec, the moisture present on the wick will tend to evaporate, making the surrounding thin film of air saturated. For evaporation the heat required is picked up from the surrounding air making the temp. of the air down. This decreased temp. of the surrounding air is named as wet bulb temp.

$$\Rightarrow DBT > WB T_2$$

Dew point temp:-

Let us consider a mixture of air and water vapour at 314 K and atm. press with a relative humidity of 30%. Calculate the vapour pressure.

$$P_v = 2.33 \text{ KPa}, R_h = 30\%$$

(304 K)

$$R_h = \frac{P_v}{P_s}$$

300 K

$$P_s = 7.76$$

293 K if $R_h = 65\%$

$$P_s = 3.58$$

TL
PT
RHT



The V.P of the water at 314 K is 7.76 KPa and Partial pressure of water vapour in air is 2.33 KPa. And the absolute humidity is 0.146 kg vapour/kg dry air.

Suppose air is cooled at constant pressure, on cooling the humidity for the partial pressure of water vapour will not change initially, but vapour pressure will change as given by the Antoine eqn and thus this results in increasing the relative humidity.

Then the temp of air drops to 300 K the VP of water drops to 3.58 KPa. Such the relative saturation in this case is 65%. On further cooling the temp will be reached at which the V.P of water is equal to the partial press. of water vapour in the air. The air becomes saturated with the water vapour present in it. This temp is known as dew pt temp. and for air it is 293 K.

Dewpt. is the lowest temp. to which a gas ^{vapour} mixture can be cooled w/o condensation at constant pressure.

It is temp at which the vapour just begins to condensed when cooled at constant pressure.

OR

The dew pt. is the temp at which the existing vapour content is sufficient to saturate the gas.

OR

Dew pt is that temp at which the vapour pressure of the ^{water} vapour is equal to the partial pressure of the vapour in the given vapour gas mixture


$$T_s = T_v$$

At the dew pt. the humidity of the air-water vapour system is the saturation humidity, which can be calculated by using the vapour pressure data or humidity chart.

Aug 12, 14

Leaching

It is a process of separation of soluble constituent of a solid material using a suitable solvent.



$$F + S = M, \quad M = O + U$$

$$F x_c + S y_c = M x_c$$

$$O y_c + U x_c = M x_c$$

* Valuable pelt is the soluble material and residue solid is generally a waste.

for ex → Extraction of oil from oil seeds.

Sometimes residue solid is a valuable pelt.

for ex → Extraction of non-protein solids.

* In leaching, a substantial part of solid doesn't dissolve

Rate of extraction depends upon

i) Solvent - non-toxic, flammable, cheap etc.

ii)

Physical Characteristics of Solid :-

⇒ For the porous, powder form. the rate of extraction in general will be high.

Agitation

Rate of extraction ↑ with increase in rate of agitation.

Temperature


As temp ↑, rate of extraction ↑
as (solubility ↑)
(viscosity ↓)



Contacting Pattern :-


* This solvent is recirculated again again till definite concentration in exit stream is achieved.

channel forming (be2 of which mixing is not proper) M.T ↓
less amt of solvent is required.




* Solvent amt required is very high.

⇒ Proper mixing.



Supercritical Fluid Extraction



The fluid is called supercritical if both temp. and pressure are above critical values. At super critical state a fluid remains as a highly condensed phase and may have a density even more than its density in the liquid state. Critical pt. is a pt. of a material above which ~~distinction~~ distinction b/w liq. & gas becomes impossible.

Supercritical fluid shares the properties of both gas and liquid, its viscosity remains somewhat smaller than the normal liquid viscosity and the diffusivity of solute in the super critical fluid. becomes high than the normal solvent.

Adsorption

The phenomena of attracting and retaining the molecules of a substance on the surface of a solid resulting into a higher concentration of the molecules on the surface is known as adsorption.

In adsorption the molecules of a substance are present in higher concentration at the surface of the solid material. ($\therefore$ it is a surface phenomena), whereas in absorption, the molecules of a substance are uniformly distributed throughout the body of a liquid. Therefore it is a bulk phenomena.

The substance on the surface of which adsorption takes place is called adsorbent and the substance adsorbed is known as adsorbate.

The process of removal of adsorbed substance from the surface on which it is adsorbed is known as desorption.

Sometimes adsorption and absorption takes place simultaneously and this process is known as sorption.

Types of Adsorption

Physical Adsorption

Adsorbate is held on the surface by weak van der Waals forces.

It is like a physical process
eg $\rightarrow$ Condensation.

The enthalpy of adsorption is of the order of 20 kJ/mole .

Chemical Adsorption

Adsorbate is held on the surface by chemical bonds.

It features a chemical process like a chemical rxn.

The enthalpy of adsorption is of the order of 200 kJ/mole .

The enthalpy change for adsorption of 1 mole of an adsorbate on adsorbent surface is called enthalpy of adsorption.

Usually takes place at low temp & decreases w/ $\uparrow$ (temp)

It is not specific, all the gases are adsorbed to some extent on all the solid.

Multi molecular layer may form.

Usually takes place at relatively high temp.

Highly specific in nature.

Single layer will form.



Adsorption Isotherms :-

The extent of adsorption of a gas on a solid is expressed by x/m , where m is the mass of adsorbent and x is no of moles of adsorbate.


A relation between x/m and pressure of gas at constant temperature is known as Adsorption Isotherms.

1) Freundlich Adsorption Isotherm

$$\boxed{\frac{x}{m} = k p^{1/n}}$$

$$\boxed{\ln \frac{x}{m} = \ln k + \frac{1}{n} \ln p}$$

$$y = \text{intercept} + mx$$



It fails when press. is very high.

2> Langmuir Adsorption Isotherm


$$\boxed{\frac{x}{m} = \frac{aP}{1+bP}}$$

$$\boxed{\frac{x}{m} = aP}$$

low pressure.

$$\boxed{\frac{x}{m} = \frac{a}{b}}$$


high Pressure



$$\frac{1}{x/m} = \frac{1+bP}{aP}$$

$$\boxed{\frac{1}{x/m} = \frac{1}{aP} + \frac{b}{a}}$$

$$y = mx + c$$



or

Adsorption Isobar:-

A relation b/w extent of adsorption and temp of gas at constant pressure is known as adsorption Isobar.